

ELECTRICAL CHARACTERISTICS


Effective Arc Length

Burn Position	Universal burning position			
Open Circuit Voltage (RMS lag ballast) (MIN)	110 V			
Warm Up Time to 90% (MIN)	3 min			
Warm Up Time to 90% (MAX)	4 min			
Hot Restart Time to 90% (MAX)	0.670 min			

1.400000 in (35.560000 mm)

GRAPHS & CHARTS

Spectral Power Distribution



DIMENSIONS

Maximum Overall Length (MOL)	5.5000 in (139.7 mm)
Nominal Length	5.500 in (139.7 mm)
Bulb Diameter (DIA)	2.125 in (53.9 mm)
Light Center Length (LCL)	3.430 in (87.1 mm)

PRODUCT INFORMATION

http://genet.gelighting.com/LightProducts/Dispatcher?REQUEST=COMMERCIALSPEC... 4/28/2009

Product Code	13250
Description	LU100/MED/ECO
ANSI Code	S54
Standard Package	Case
Standard Package GTIN	10043168132500
Standard Package Quantity	6
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	6
UPC	043168132503

COMPATIBLE GE BALLASTS

Product Code	Description	# of Bulbs	Power Factor	Ballast Factor
<u>87068</u>	GES10048TLC3D- 5	1	90.0	1.0
<u>87074</u>	GES100MLTLC3D- 5	1	90.0	1.0
<u>71705</u>	GES100MLTLC3D- 55	1	90.0	1.0

A CAUTIONS & WARNINGS

See list of cautions & warnings.

Return To Top

Home | Products | EliteNet | Education/Resources | Lighting Applications | Where to Buy | FAQs | Contact Us | Site Map Products for Your Home | Press Room | Corporate | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use

Copyright General Electric Company 1997-2009