

A



TYPE HT

Features

- Serrated interior
- Prefilled with oxide inhibitor
- Installed with industry standard "O" and "D" dies
- Manufactured from high strength aluminum alloy
- Suitable for use in circuits rated 35KV or less, proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Assures positive mating with cable strands when compressed
- Provides corrosion resistance
- Provides convenient die selection
- Provides maximum conductivity and excellent crimping characteristics
- Application versatility



Catalog Number	Wire Range										Program Number	Connector Die	No. of Crimps		Dimensions											
	Standard Wire						Compact Wire						Mech. Tool	Hyd. Tool	L	W	H									
	A Groove ACSR	str	sol	B Groove ACSR	str	sol	A Groove ACSR	str	B Groove ACSR	str																
HT-6	2, 3, 4, 6, - -	1, 2, 3, 4, 6 -	1, 2, 3, 4, 6 -	2, 3, 4, 6 -	1, 2, 3, 4, 6 -	1, 2, 3, 4, 6 -	2, 3, 4, 6 -	1, 2, 3, 4, 6 -	1, 2, 3, 4, 6 -	1, 2, 3, 4, 6 -	1	O O O O O O	4 4 4 4 4 4	2 2 2 2 2 2	1-1/2	23/32	1-23/32									
HT-8	1/0, 1, 2, 3 - -	2/0, 1/0, 1, 2 - -	3/0, 2/0, 1/0, 1 - -	2, 3, 4, 6 -	1, 2, 3, 4, 6 -	1/0, 1, 2, 3, 4, 6 -	2/0, 1/0, 1, 2 -	2/0, 1/0, 1, 2 -	1, 2, 3, 4, 6 -	1, 2, 3, 4, 6 -	2	O O O O O O	5 5 5 5 5 5	2 2 2 2 2 2				1-1/2	45/64	1-25/32						
HT-2	2/0, 1/0 - - -	3/0, 2/0 - - -	- - - -	2, 3, 4, 6 -	1, 2, 3, 4, 6 -	1/0, 1, 2, 3, 4, 6 -	3/0, 2/0 - - -	3/0 - - -	1, 2, 3, 4, 6 -	1, 2, 3, 4, 6 -	3	D3 D3 D3 D3 D3	5 5 5 5 5	2 2 2 2 2							1-7/8	13/16	2-3/16			
HT-4	2/0, 1/0, 1	3/0, 2/0, 1/0	- - -	2/0, 1/0, 1	3/0, 2/0, 1/0	- - -	3/0, 2/0, 1/0	3/0, 2/0, 1/0	3/0, 2/0, 1/0	3/0, 2/0, 1/0	4	D3 D3 D3	6 6 6	2 2 2										1-7/8	57/64	2-17/64
HT-3	4/0, 3/0 - - -	4/0 - - -	- - - -	2, 3, 4, 6 -	1, 2, 3, 4, 6 -	1/0, 1, 2, 3, 4, 6 -	266, 4/0 - - -	266, 250, 4/0 - - -	1, 2, 3, 4, 6 -	1, 2, 3, 4, 6 -	5	D3 D3 D3 D3 D3	5 5 5 5 5	2 2 2 2 2												
HT-5	4/0, 3/0 -	4/0, 3/0 -	- - -	2/0, 1/0 -	2/0, 1/0 -	- - -	266, 4/0, 3/0	266, 250, 4/0	2/0, 1/0 -	3/0, 2/0, 1/0	6	D3 D3 D3	7 7 7	3 3 3	2-1/4	53/64	2-3/8									
HT-7	4/0, 3/0 -	4/0, 3/0 -	- - -	4/0, 3/0 -	4/0, 3/0 -	- - -	266, 4/0, 3/0	266, 250, 4/0	266, 4/0, 3/0	266, 250, 4/0	7	D3 D3 D3	7 7 7	3 3 3				2-1/2	7/8	2-1/2						

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
 Consult factory for tool and die information.