

• TRUSTED QUALITY SINCE 1921 •  
**RUST-OLEUM®**  
 INDUSTRIAL  
 — CHOICE —

## M1400 SYSTEM CONSTRUCTION MARKING PAINT AEROSOL

### DESCRIPTION AND USES

A general purpose water-based marking paint designed for marking gravel, grass, dirt, asphalt, concrete, rock, and more. Ideal for use in a variety of industries including utility location, surveying, excavation, construction, golf courses, landscaping, mining and HVAC.

Available in both solvent based and water based formulations.

### PRODUCTS

#### SOLVENT BASED

SKU	DESCRIPTION
331774	Clear
331775	White
331776	Caution Blue
331777	High Visibility Yellow
331778	Safety Red
331779	Fluorescent Orange
331780	Fluorescent Pink
331781	Fluorescent Red Orange
331782	Fluorescent Green
359823	Black

#### WATER BASED

SKU	DESCRIPTION
264692	White
264693	Clear
264964	Caution Blue
264695	High Visibility Yellow
264696	Safety Red
264697	Fluorescent Orange
264699	Fluorescent Red Orange
264700	Fluorescent Green
264702	Fluorescent Pink
314062	Safety Green
316312	Safety Purple
359824	Black

**NOTE:** Inverted 20 fl. oz. aerosol container, (17 oz. fill weight), 12 aerosols/carton.

### PRODUCT APPLICATION

#### SURFACE PREPARATION

ALL SURFACES: Remove loose contaminants by sweeping the surface before application of the coating.

#### APPLICATION

Use when temperature is 40-90°F (10-32°C) and humidity is below 85% to ensure proper drying. This product can be used down to 25°F (-4°C) which may result in a slight reduction of delivery rate. Protect surrounding surfaces from overspray. Overspray can carry a significant distance. Shake can vigorously for one minute after mixing ball is heard. Hold can 4 to 10 inches from surface to be marked. Press spray tip sideways to spray or use Rust-Oleum Marking Wand #2393000 or Marking Pistol #210188. Follow directions for proper use of this equipment. Keep can moving to prevent build-up.

#### DRY & RECOAT TIMES

Dry and recoat times are based on 70°F and 50% relative humidity. This product dries in less than 5 minutes.

#### CLEAN-UP

Wipe off spray tip when finished using. Properly discard empty container. Do not burn or place in trash compactor. Empty container can be recycled.

<b>AEROSOL</b>	<b>TECHNICAL DATA</b>	<b>IC-09</b>
<small>• TRUSTED QUALITY SINCE 1921 •</small> <b>RUST-OLEUM®</b> INDUSTRIAL — CHOICE —	<b>M1400 SYSTEM</b> <b>CONSTRUCTION MARKING PAINT AEROSOL</b>	

**PHYSICAL PROPERTIES**

	<b>CONSTRUCTION MARKING PAINT</b>	
	<b>Solvent Based</b>	<b>Water Based</b>
<b>Resin Type</b>	Acrylic Modified Alkyd	Acrylic Modified Alkyd
<b>Pigment Type</b>	Varies with color	Varies with color
<b>Solvents</b>	Mineral Spirits, Naphtha, Acetone, Xylene	Water, Acetone, Mineral Spirits, Naphtha, Xylene
<b>MIR</b>	Maximum value of 0.85	Maximum value of 0.85
<b>Fill Weight</b>	17 oz.	17 oz.
<b>Practical Coverage</b>	Approximately 400 linear feet at 1 inch wide	Approximately 400 linear feet at 1 inch wide
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	Less than 5 minutes	Less than 5 minutes
<b>Shelf Life</b>	5 years	5 years
<b>Safety Information</b>	For additional information, see SDS	

Calculated values are shown and may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation  
11 Hawthorn Parkway  
Vernon Hills, Illinois 60061

Phone: 877-385-8155  
[www.rustoleum.com/industrial](http://www.rustoleum.com/industrial)

Form: GDH-1049  
Rev.: 052220