

## Specifications

Blade Material

Hardened Steel

Capacity

5-40 in. lbs

Handle Type

Triangular and Textured

Includes

Torque Driver Phillips #1 x3-1/2" (88.9 mm) Phillips #2x 3-1/2" (88.9 mm) Slotted 3/16" (4.76 mm) x 3-1/2" (88.9 mm) Slotted 1/4" (6.35 mm) x 3-1/2" (88.9 mm) Square #1 x 3-1/2" (88.9 mm) Square #2 x 3-1/2" (88.9 mm) Phillips #1 x 6" (152.4 mm) Phillips #2x 6" (152.4 mm) Slotted 3/16" (4.76 mm) x 6" (152.4 mm) Slotted 1/4" (6.35 mm) x 6" (152.4 mm) Square #1 x 6" (152.4 mm) Square #2 x 6" (152.4mm) Nut Driver 3/16" (4.76 mm) x 6" (152.4 mm) Nut Driver 1/4" (6.35 mm) x 6" (152.4 mm) Nut Driver 5/16" (7.94 mm) x 6" (152.4 mm) Nut Driver 11/32" (8.73 mm) x 6" (152.4mm) Nut Driver 3/8" (9.53 mm) x 6" (152.4 mm) Nut Driver 7/16" (11.11 mm) x 6" (152.4mm) Nut Driver 1/2" (12.7 mm)x 6" (152.4 mm) Carrying Case

Overall Length

5.13"

Replacement Part

Replacement Bit Set: 9953-46T Replacement Case: 0153-46 Case

Shank Length

3-1/2" (88.9 mm) & 6" (152.4 MM)

Shank Shape

Round

Type

Torque