

## Toggle Switches



Versatile toggle switch family with multiple position configurations.

- Available in single or double pole.
- Perfect for industrial equipment or emergency lighting.
- 1/2" mounting hole required.
- **Specifications:** 10 A, 277 V AC / 20 A, 125 V AC

**tip:** All switches must be installed with a hex nut (provided) behind panel to prevent damage during installation.

<b>Part Number</b>	<b>GWS-10</b>	<b>GWS-11*</b>	<b>GWS-110</b>	<b>GWS-121</b>
<b>Poles</b>	<b>SPST</b>			
<b>Pkg Qty</b>	1/card	1/card	1/card	1/card
<b>Toggle Position</b>	ON-OFF	ON-OFF	ON-OFF	ON-OFF
<b>Terminal Type</b>	Screw	Screw	"O" Ring & Screw	Spade
<b>Rating</b>	1½ HP 125-250 V AC	¾ HP 125-250 V AC	¾ HP 125-250 V AC	¾ HP 125-250 V AC

\*GWS-11 has an ON-OFF faceplate.

<b>Part Number</b>	<b>GWS-12</b>	<b>GWS-13</b>	<b>GWS-120</b>	<b>GWS-117</b>
<b>Poles</b>	<b>SPDT</b>			
<b>Pkg Qty</b>	1/card	1/card	1/card	1/card
<b>Toggle Position</b>	ON-ON	ON-OFF-ON	ON-OFF-ON	(ON)-OFF-(ON)
<b>Terminal Type</b>	Screw	Screw	Spade	Screw
<b>Rating</b>	¾ HP 125-250 V AC	¾ HP 125-250 V AC	¾ HP 125-250 V AC	¾ HP 125-250 V AC

( ) Indicates momentary action

<b>Part Number</b>	<b>GWS-14</b>	<b>GWS-15</b>	<b>GWS-16</b>	<b>GWS-123</b>
<b>Poles</b>	<b>DPST</b>		<b>DPDT</b>	
<b>Pkg Qty</b>	1/card	1/card	1/card	1/card
<b>Toggle Position</b>	ON-OFF	ON-ON	ON-OFF-ON	(ON)-OFF-(ON)
<b>Terminal Type</b>	Screw	Screw	Screw	Screw
<b>Rating</b>	1½ HP 125-250 V AC	1½ HP 125-250 V AC	1½ HP 125-250 V AC	1½ HP 125-250 V AC

( ) Indicates momentary action

<b>Part Number</b>	<b>GWS-17*</b>	<b>GWS-18*</b>	<b>GWS-124</b>	<b>GWS-125</b>	<b>GWS-125BP</b>
<b>Poles</b>	<b>SPST</b>				
<b>Pkg Qty</b>	1/card	1/card	1/card	1/card	10/box
<b>Toggle Position</b>	ON-OFF	ON-OFF	ON-OFF	ON-OFF	ON-OFF
<b>Terminal Type</b>	Screw	6" wire leads	screw	6" wire leads	6" wire leads
<b>Actuator</b>	bat lever	bat lever	short ball	short ball	short ball
<b>Rating</b>	3 A/240 V AC, 6 A/120 V AC	8 A/125 V, 4 A/250 V, 1/3 HP/125 V AC, 10 A/125 V AC	3 A/240 V AC, 6 A/120 V AC	3 A/250 V, 6 A/125 V	3 A/250 V, 6 A/125 V

( ) Indicates momentary action \*GWS-17 & 18 have an ON-OFF faceplate.