

Thin-Wall Heat-Shrink Tubing – Polyolefin

Great for cable insulation, marking and bundling, with superior mechanical, abrasion and moisture protection.

- Flame retardant, meets UL 224 VW-1.
- Resists common fluids and solvents.
- Meets UL 224, 125°C; CSA C22.2 No. 198.1, 125°C; MIL-DTL-23053/5, Class 1 & 2, AMS 3636 & 3637; DEF Stan 59-79, Issue 3 Type 2a.
- Continuous operating temperature: -40°C (40°F) - 125°C (257°F).
- Shrink temperature: 125°C (257°F) - 250°C (480°F).
- 600 V/Mil Dielectric strength.
- 2:1 shrink ratio.
- Material is Polyolefin.



Part #	Pkg Qty	Before	Finished	Length	Conductor Gauge AWG*																Color
					24	22	20	18	16	14	12	10	8	6	4	2	1	1/O	2/O	3/O	
HST-093	8 pcs	3/32"	3/64"	4"	●																Black
HST-093B	8/clam	3/32"	3/64"	3"	●																Black
HST-093W	8/clam	3/32"	3/64"	3"	●																White
HST-093R	8/clam	3/32"	3/64"	3"	●																Red
HST-125	7 pcs	1/8"	1/16"	4"		●	●	●													Black
HST-125B	8/clam	1/8"	1/16"	3"		●	●	●													Black
HST-125B6	10/clam	1/8"	1/16"	6"		●	●	●													Black
HST-125R	8/clam	1/8"	1/16"	3"		●	●	●													Red
HST-125W6	10/clam	1/8"	1/16"	6"		●	●	●													White
HST-100	1 pc	3/16"	3/32"	8'			●	●	●	●	●										Red
HST-187W	8 pcs	3/16"	3/32"	4"			●	●	●	●	●										Black
HST-187W	5/clam	3/16"	3/32"	3"			●	●	●	●	●										White
HST-101	1 pc	1/4"	1/8"	8'				●	●	●	●	●									Blue
HST-101B	1/clam	1/4"	1/8"	8'				●	●	●	●	●									Black
HST-250	6 pcs	1/4"	1/8"	4"				●	●	●	●	●									Black
HST-250B	5/clam	1/4"	1/8"	3"				●	●	●	●	●									Black
HST-250R	5/clam	1/4"	1/8"	3"				●	●	●	●	●									Red
HST-250W	5/clam	1/4"	1/8"	3"				●	●	●	●	●									White
HST-102	1 pc	5/16"	5/32"	8"						●	●	●	●	●							Yellow
HST-375	3 pcs	3/8"	3/16"	4"							●	●	●	●	●						Black
HST-500	3 pcs	1/2"	1/4"	4"								●	●	●	●						Black
HST-750	2 pcs	3/4"	3/8"	4"											●	●	●	●	●	●	Black
HST-750B	2/clam	3/4"	3/8"	3"											●	●	●	●	●	●	Black
HST-750B6	4/clam	3/4"	3/8"	6"											●	●	●	●	●	●	Black
HST-750R	2/clam	3/4"	3/8"	3"											●	●	●	●	●	●	Red
HST-999	2 pcs	1"	1/2"	4"														●	●	●	Black
HST-999B	2/clam	1"	1/2"	3"														●	●	●	Black
HST-999R	2/clam	1"	1/2"	3"														●	●	●	Red
HST-999W	2/clam	1"	1/2"	3"														●	●	●	White
XTM-301	8/clam	3/16", 3/4"	3/32", 3/8"	3"																	Black
HST-ASTB	160/kit	3/32", 1/8", 3/16", 1/4", 3/4", 1/16", 3/8"	3/64", 1/16", 3/32", 1/8", 3/8", 1/32", 3/16"	3"																	Black
XTM-305	5/clam	3/8"		3"																	Assorted (Red, Blue, Yellow)
HST-107	7 pcs	1/8", 1/4", 3/8", 1/2"	1/16", 1/8", 3/16", 1/4"	3"																	Assorted (Red, Blue, Yellow)
HST-ASTA	160/kit	3/32", 1/8", 3/16", 1/4", 3/4", 1/16", 3/8"	3/64", 1/16", 3/32", 1/8", 3/8", 1/32", 3/16"	3"																	Assorted (Red, Blue, Yellow)

*Sizes shown are approximate and may vary according to manufacturer and insulation system for each wire.

XTM-301 and XTM-307 are **GB Xtreme**® products.