

Application	Wire Termination
Brand	NSi
Catalog Description	6 Wire Polaris Vision Tap 350 MCM - 6 AWG Insulated Multi-Cable Connector Block, Either Side Wire Entry Polaris Vision Tap Connectors have wire entry ports on both sides of the connector to allow for access from either side. Eliminates the need for cover and taping. Insulated with high-dielectric strength plastisol. Molded for precise fit and supplied with removable plugs to close the entry port not being utilized. Abrasion and chemical resistant. Will not support combustion. AL9CU. Cold temperature rated to -45 degrees C, rated 600V, 90 degrees C. Dual rated for use with copper and/or aluminum cables. Not recommended for fine-stranded, flexible wire.
Enclosure	Clear Plastisol
Environmental Conditions	Dry Location Only
Finish	Plastisol
Finish 2	Colorless
Height	2.6100
Height Unit	IN
Item Status	A
Length	6.6700
Length UOM	IN
Material	Plastisol
Mfr. #	IPLD350-6C
Number Of Conductors	6
Number Of Poles	1
Ships Freight	No
Ships Ground. Eligible for expedited shipping	Yes
Size	L=6.670 - W=2.410 - H=2.610
Special Features	(6) 350 MCM-6 AWG - Dual Rated
Standard	cULus
Sub-Brand	Polaris Vision Tap
Temperature Rating	90
Type	Double Sided Entry
Voltage Rating	600
Width	2.4100
Width UOM	IN
Wire Size	350 MCM-6 AWG
Wire Type	Class B & C