







Covers and Gaskets for Form 35® Unilet® Conduit Outlet Bodies




Covers Furnished with Stainless Steel Fastening Screws.

Appleton Form 35® Covers and Gaskets NOTE: Refer to page A-16 for Wiring Capacity Tables.

Size	Blank Stamped Steel	Blank Cast Malleable	Neoprene	Composition Fiber
Form 35 Body Size (in.)	 Domed: 1/2" - 3"	 Flat: 1/2" - 2"	 Tear out inner perforated section to convert to "open type" gasket.	
	 Flat: 3-1/2" - 6"	 Domed: 2-1/2" - 4"		
1/2	K50	K50-CM	GK50-N	GK50-V
3/4	K75	K75-CM	GK75-N	GK75-V
1	K100	K100-CM	GK100-N	GK100-V
1-1/4	K125 & 150	K125 & 150-CM	GK125-150-N	GK125-150-V
1-1/2	K125 & 150	K125 & 150-CM	GK125-150-N	GK125-150-V
2	K200	K200-CM	GK200-N	GK200-V
2-1/2	K250 & 300	K250 & 300-CM	GK250-300-N	GK-250-300-V
3	K250 & 300	K250 & 300-CM	GK250-300-N	GK-250-300-V
3-1/2	K350 & 400	K350 & 400-CM	GK350-400-N	GK-350-400-V
4	K350 & 400	K350 & 400-CM	GK350-400-N	GK-350-400-V
5	K500	—	GK500-SN†	
6	K600	—	GK600-SN†	

† Not perforated

Wiring Device Covers

		
Lamp Receptacle with 1-1/2" Shade Holder Groove. Porcelain, 600 Watt, 600 Volt Rating	Device Cover for Interchangeable (Despard) Wiring Devices, Cast Aluminum with Mounting Strap	Switch Cover for Interchangeable (Despard) Devices, Cast Aluminum with Gasket and Steel Mounting Strap
Form 35 Body Size (in.) Cat. No.	Form 35 Body Size (in.) Cat. No.	Form 35 Body Size (in.) Cat. No.
1/2 KLR50	1/2 KWD50-A	3/4 KVS75-A
3/4 KLR75		