







## Covers and Gaskets for Form 35® Unilet® Conduit Outlet Bodies




Covers Furnished with Stainless Steel Fastening Screws.

**Appleton Form 35® Covers and Gaskets** NOTE: Refer to page A-16 for Wiring Capacity Tables.

Size	Blank Stamped Steel	Blank Cast Malleable	Neoprene	Composition Fiber
Form 35 Body Size (in.)	 Domed: 1/2" - 3"	 Flat: 1/2" - 2"	 Tear out inner perforated section to convert to "open type" gasket.	
	 Flat: 3-1/2" - 6"	 Domed: 2-1/2" - 4"		
1/2	K50	K50-CM	GK50-N	GK50-V
3/4	K75	K75-CM	GK75-N	GK75-V
1	K100	K100-CM	GK100-N	GK100-V
1-1/4	K125 & 150	K125 & 150-CM	GK125-150-N	GK125-150-V
1-1/2	K125 & 150	K125 & 150-CM	GK125-150-N	GK125-150-V
2	K200	K200-CM	GK200-N	GK200-V
2-1/2	K250 & 300	K250 & 300-CM	GK250-300-N	GK-250-300-V
3	K250 & 300	K250 & 300-CM	GK250-300-N	GK-250-300-V
3-1/2	K350 & 400	K350 & 400-CM	GK350-400-N	GK-350-400-V
4	K350 & 400	K350 & 400-CM	GK350-400-N	GK-350-400-V
5	K500	—	GK500-SN†	
6	K600	—	GK600-SN†	

† Not perforated

### Wiring Device Covers

		
<b>Lamp Receptacle</b> with 1-1/2" Shade Holder Groove. Porcelain, 600 Watt, 600 Volt Rating	<b>Device Cover</b> for Interchangeable (Despard) Wiring Devices, Cast Aluminum with Mounting Strap	<b>Switch Cover</b> for Interchangeable (Despard) Devices, Cast Aluminum with Gasket and Steel Mounting Strap
<b>Form 35 Body Size (in.)</b> <b>Cat. No.</b>	<b>Form 35 Body Size (in.)</b> <b>Cat. No.</b>	<b>Form 35 Body Size (in.)</b> <b>Cat. No.</b>
1/2 <b>KLR50</b>	1/2 <b>KWD50-A</b>	3/4 <b>KVS75-A</b>
3/4 <b>KLR75</b>		