

## Variable Speed & Two Circuit Pull-Chain Switches



Pull chain switches for multifunction applications.



- Two and three speed switching.
- Push-in connections for #18 AWG wire.
- Mounts in 1 $\frac{1}{32}$ " diameter hole.
- **Specifications:** 6 A/125 V AC, 3 A/250 V AC, 6 A/125 VL; 75°C max. temp rating.

|                        |               |               |                             |
|------------------------|---------------|---------------|-----------------------------|
|                        |               |               |                             |
| <b>Part Number</b>     | <b>GSW-33</b> | <b>GSW-34</b> | <b>GSW-39</b>               |
| <b>Poles</b>           | <b>SPDT</b>   | <b>SP3T</b>   | <b>DP3T</b>                 |
| <b>Pkg Qty</b>         | 1/card        | 10/box        | 1/card                      |
| <b>Toggle Position</b> | OFF-ON-ON     | OFF-ON-ON-ON  | OFF-ON(A)-ON(B)<br>-ON(A+B) |
| <b>Terminal Type</b>   | wire leads    | wire leads    | 6" wire leads               |
| <b>Plating</b>         | Brass         | Brass         | Brass                       |
| <b>Circuit</b>         | 3 Pos. 3 Wire | 4 Pos. 4 Wire | 4 Pos. 3 Wire               |

## Standard Rocker Switches



Heavy-duty rocker switches that fit .830" X 1.45" panel cutouts.



- Frame and rocker are black glass-filled nylon.
- Lighted or unlighted versions available.
- **Specifications:** 10 A/277 V AC, 20 A/125 V AC; 75°C max. temp rating.
- Switches with solder terminals come in a phenolic case and do not have a moisture and dust resistant seal.



## Appliance Rocker Switches

Economy rocker switches that fit standard .550" X 1.125" panel cutouts.

- Perfect for machinery or appliances.
- Lighted or unlighted versions available.
- **Specifications:** 16 A/125 V AC, 8 A/250 V AC; 75°C max. temp rating.

|                        |                     |                     |
|------------------------|---------------------|---------------------|
|                        |                     |                     |
| <b>Part Number</b>     | <b>GSW-45</b>       | <b>GSW-49*</b>      |
| <b>Poles</b>           | <b>SPST</b>         |                     |
| <b>Pkg Qty</b>         | 1/card              | 1/card              |
| <b>Toggle Position</b> | ON-OFF              | ON-OFF              |
| <b>Terminal Type</b>   | spade               | spade               |
| <b>Rating</b>          | ½ HP 125 - 250 V AC | ½ HP 125 - 250 V AC |

\*Red lighted

|                        |               |                |
|------------------------|---------------|----------------|
|                        |               |                |
| <b>Part Number</b>     | <b>GSW-41</b> | <b>GSW-42*</b> |
| <b>Poles</b>           | <b>SPST</b>   |                |
| <b>Pkg Qty</b>         | 1/card        | 1/card         |
| <b>Toggle Position</b> | ON-OFF        | ON-OFF         |
| <b>Terminal Type</b>   | spade         | spade          |

\*Red lighted

## Mini Rocker Switch



Miniature rocker switch that fits .520" X .776" panel cutouts.



- Perfect for small machinery or appliances.
- **Specifications:** 13 A/125 V AC, 10 A/250 V AC, ½ HP 125 - 250 V AC; 75°C max. temp rating.



| Part #         | Pkg Qty | Poles       | Toggle Position | Terminal Type | Rated  |
|----------------|---------|-------------|-----------------|---------------|--|
| <b>GSW-48*</b> | 1/card  | <b>SPST</b> | ON-OFF          | spade         | 10 A/125 - 250 V AC,<br>½ HP 250 V AC, ½ HP 125 V AC |

\*Red lighted