



**Friendly Service ... Powerful Solutions**

## Topaz Specification Sheet


**Description:** Compression type connector used to join EMT to box or enclosure

**Standard Material:** Steel

**Standard Finish:** Zinc Plated

**Features:** Concrete Tight. Assembled with a Steel Locknut

UL Standard: 514B  
Fed .Spec. W-F-408E  
NEMA: FB-1



TOPAZ CAT#	A	B	C
651S/Si	1.750	1.250	.406
652S/Si	1.813	1.563	.406
653S/Si	2.000	1.813	.406
654S/Si	2.750	2.188	.500
655S/Si	3.000	2.438	.500
656S/Si	3.188	2.938	.688
657S/Si	3.875	3.688	.750
658S/Si	4.375	4.313	.938
659S/Si	4.500	4.875	.938
660S/Si	4.750	5.375	.938

TOPAZ CAT #	UPC#	SIZE	UNIT CTN	SHIP CASE	WT/ CASE
651S	16790	1/2"	25	250	30
652S	16800	3/4"	25	250	43
653S	16810	1"	10	100	25
654S	16820	1 1/4"	—	25	12
655S	16830	1 1/2"	—	20	12
656S	16840	2"	—	15	15
657S	16841	2 1/2"	—	12	19
658S	16842	3"	—	6	15
659S	16843	3 1/2"	—	6	16
660S	16844	4"	—	6	21

### INSULATED THROAT

651Si	16850	1/2"	25	250	30
652Si	16860	3/4"	25	250	43
653Si	16870	1"	10	100	25
654Si	16880	1 1/4"	—	25	12
655Si	16890	1 1/2"	—	20	12
656Si	16900	2"	—	15	15
657Si	16901	2 1/2"	—	12	19
658Si	16902	3"	—	6	15
659Si	16903	3 1/2"	—	6	16
660Si	16904	4"	—	6	21



E148716



E148716

Approved by Quality Control: John Cavalieri



**NEW YORK**  
925 Waverly Avenue  
Holtsville, NY 11742  
800-666-2852  
Fax: 800-333-3488

**CALIFORNIA**  
225 Parkside Drive  
San Fernando, CA 91340  
888-551-2852  
Fax: 888-690-2852

**FLORIDA**  
2020 West 26th Street  
Jacksonville, FL 32209  
800-666-2852  
Fax: 800-333-3488