



Friendly Service ... Powerful Solutions

Topaz Specification Sheet


Description: Compression type connector used to join EMT to box or enclosure

Standard Material: Steel

Standard Finish: Zinc Plated

Features: Concrete Tight. Assembled with a Steel Locknut

UL Standard: 514B
Fed .Spec. W-F-408E
NEMA: FB-1



| TOPAZ CAT# | A | B | C |
|------------|-------|-------|------|
| 651S/Si | 1.750 | 1.250 | .406 |
| 652S/Si | 1.813 | 1.563 | .406 |
| 653S/Si | 2.000 | 1.813 | .406 |
| 654S/Si | 2.750 | 2.188 | .500 |
| 655S/Si | 3.000 | 2.438 | .500 |
| 656S/Si | 3.188 | 2.938 | .688 |
| 657S/Si | 3.875 | 3.688 | .750 |
| 658S/Si | 4.375 | 4.313 | .938 |
| 659S/Si | 4.500 | 4.875 | .938 |
| 660S/Si | 4.750 | 5.375 | .938 |

| TOPAZ CAT # | UPC# | SIZE | UNIT CTN | SHIP CASE | WT/ CASE |
|-------------|-------|--------|----------|-----------|----------|
| 651S | 16790 | 1/2" | 25 | 250 | 30 |
| 652S | 16800 | 3/4" | 25 | 250 | 43 |
| 653S | 16810 | 1" | 10 | 100 | 25 |
| 654S | 16820 | 1 1/4" | — | 25 | 12 |
| 655S | 16830 | 1 1/2" | — | 20 | 12 |
| 656S | 16840 | 2" | — | 15 | 15 |
| 657S | 16841 | 2 1/2" | — | 12 | 19 |
| 658S | 16842 | 3" | — | 6 | 15 |
| 659S | 16843 | 3 1/2" | — | 6 | 16 |
| 660S | 16844 | 4" | — | 6 | 21 |

INSULATED THROAT

| TOPAZ CAT # | UPC# | SIZE | UNIT CTN | SHIP CASE | WT/ CASE |
|-------------|-------|--------|----------|-----------|----------|
| 651Si | 16850 | 1/2" | 25 | 250 | 30 |
| 652Si | 16860 | 3/4" | 25 | 250 | 43 |
| 653Si | 16870 | 1" | 10 | 100 | 25 |
| 654Si | 16880 | 1 1/4" | — | 25 | 12 |
| 655Si | 16890 | 1 1/2" | — | 20 | 12 |
| 656Si | 16900 | 2" | — | 15 | 15 |
| 657Si | 16901 | 2 1/2" | — | 12 | 19 |
| 658Si | 16902 | 3" | — | 6 | 15 |
| 659Si | 16903 | 3 1/2" | — | 6 | 16 |
| 660Si | 16904 | 4" | — | 6 | 21 |



E148716



E148716

Approved by Quality Control: John Cavalieri



NEW YORK
925 Waverly Avenue
Holtsville, NY 11742
800-666-2852
Fax: 800-333-3488

CALIFORNIA
225 Parkside Drive
San Fernando, CA 91340
888-551-2852
Fax: 888-690-2852

FLORIDA
2020 West 26th Street
Jacksonville, FL 32209
800-666-2852
Fax: 800-333-3488