


Bushings, Nipples, Locknuts and Plugs

Meets and surpasses NEC® requirements!

Insulated Throat Fittings

- Steel or malleable iron (steel through 1½")
- Exceeds NEC 373-6C requirements for protection of ungrounded connectors at entrance to raceways, pull boxes and junctions
- Recognizable by distinctive trademarked blue insulating liner in throat
- Reduces wire pulling effort by as much as 50%
- Temperature rating of 105° C
- Look for the unique T&B blue color, ensuring the highest quality fitting



CAT. NO.		DIMENSIONS (IN.)		
STL. OR M.I.	ALUM.	SIZE	A	B
1222	1222AL	½"	1½/32	29/64
1223	1223AL	¾"	1½/32	31/64
1224	1224AL	1"	119/32	11/32
1225	1225AL	1¼"	115/16	21/32
1226	1226AL	1½"	23/16	23/32
1227	1227AL	2"	211/16	½
1228	1228AL	2½"	33/16	½
1229	1229AL	3"	321/32	5/16
1230	1230AL	3½"	41/16	11/16
1231	1231AL	4"	47/8	13/32
1232†	1232AL†	4½"	—	—
586	586AL	5"	521/32	13/32
587	587AL	6"	73/16	113/32


† Not CSA Certified

Catalog series 1222 thru 1232, 586 and 587 are available in aluminum. Add suffix AL to Cat. No. The aluminum series fittings are not CSA certified.

Locknut-type base improves bonding and resists loosening under vibration.

Metallic Bushings

- Aluminum, steel or malleable iron (steel through 1½")
- Smoothly rounded shoulder covers end of conduit
- Broad flange covers knockout hole
- High ribs for easy tightening with fingers or with wrench
- ½" to 1½" sizes, formed in steel, feature extra-smooth shoulders



CAT. NO.		DIMENSIONS (IN.)		
STL. OR M.I.	ALUM.	SIZE	A	B
122	122AL	½"	1½/32	13/32
123	123AL*	¾"	1¼	¼
124	124AL**	1"	13/16	½
125-TB	125AL	1¼"	13/32	9/16
126	126AL	1½"	23/32	19/32
127	127AL	2"	23/32	5/8
128	128AL	2½"	33/16	¾
129	129AL	3"	321/32	13/16
130-TB	130AL	3½"	43/8	15/16
131-TB	131AL	4"	415/16	1
132-TB	—	4½"	51/16	13/16
133-TB	133AL	5"	6	13/16
134-TB	134AL	6"	7¼	1¼

* Not UL Listed or CSA Certified

UL File No. E-23018


** Not CSA Certified

CSA File No. 2884

Available with DURA-PLATE® Finish.

Perfect threads for easy thread-on!

Plastic Insulating Bushings



All Plastic Insulating Bushings

- Impact-resistant plastic insulation
- Ribbed for easy, secure gripping
- UL Listed 105° C

CAT. NO.	SIZE	DIMENSIONS (IN.)	
		A	B
222-TB	½"	11/16	3/8
223-TB	¾"	13/32	13/32
224	1"	13/16	9/16
225-TB	1¼"	129/32	9/16
226	1½"	21/32	9/16
227	2"	225/32	5/8
228-TB	2½"	33/8	¾
229-TB	3"	41/16	¾
230-TB	3½"	47/8	7/8
231	4"	51/8	1
232	4½"	511/16	1
233	5"	63/16	1
234	6"	77/16	1

UL Rated flame retardant 94V-1

