


Bushings, Nipples, Locknuts and Plugs

Meets and surpasses NEC® requirements!

Insulated Throat Fittings


- Steel or malleable iron (steel through 1½")
- Exceeds NEC 373-6C requirements for protection of ungrounded connectors at entrance to raceways, pull boxes and junctions
- Recognizable by distinctive trademarked blue insulating liner in throat
- Reduces wire pulling effort by as much as 50%
- Temperature rating of 105° C
- Look for the unique T&B blue color, ensuring the highest quality fitting



Locknut-type base improves bonding and resists loosening under vibration.

Metallic Bushings

- Aluminum, steel or malleable iron (steel through 1½")
- Smoothly rounded shoulder covers end of conduit
- Broad flange covers knockout hole
- High ribs for easy tightening with fingers or with wrench
- ½" to 1½" sizes, formed in steel, feature extra-smooth shoulders



| CAT. NO. | | DIMENSIONS (IN.) | | |
|--------------|---------|------------------|--------|--------|
| STL. OR M.I. | ALUM. | SIZE | A | B |
| 1222 | 1222AL | ½" | 1½/32 | 29/64 |
| 1223 | 1223AL | ¾" | 1½/32 | 31/64 |
| 1224 | 1224AL | 1" | 119/32 | 11/32 |
| 1225 | 1225AL | 1¼" | 115/16 | 21/32 |
| 1226 | 1226AL | 1½" | 23/16 | 23/32 |
| 1227 | 1227AL | 2" | 211/16 | ½ |
| 1228 | 1228AL | 2½" | 33/16 | 1/32 |
| 1229 | 1229AL | 3" | 321/32 | 5/16 |
| 1230 | 1230AL | 3½" | 41/16 | 11/16 |
| 1231 | 1231AL | 4" | 47/8 | 13/32 |
| 1232† | 1232AL† | 4½" | — | — |
| 586 | 586AL | 5" | 521/32 | 13/32 |
| 587 | 587AL | 6" | 73/16 | 113/32 |

† Not CSA Certified

Catalog series 1222 thru 1232, 586 and 587 are available in aluminum. Add suffix AL to Cat. No. The aluminum series fittings are not CSA certified.

| CAT. NO. | | DIMENSIONS (IN.) | | |
|--------------|---------|------------------|--------|-------|
| STL. OR M.I. | ALUM. | SIZE | A | B |
| 122 | 122AL | ½" | 1½/32 | 13/32 |
| 123 | 123AL* | ¾" | 1¼ | 1/16 |
| 124 | 124AL** | 1" | 13/16 | ½ |
| 125-TB | 125AL | 1¼" | 13/32 | 9/16 |
| 126 | 126AL | 1½" | 23/32 | 19/32 |
| 127 | 127AL | 2" | 23/32 | 5/8 |
| 128 | 128AL | 2½" | 33/16 | 3/4 |
| 129 | 129AL | 3" | 321/32 | 13/16 |
| 130-TB | 130AL | 3½" | 43/8 | 15/16 |
| 131-TB | 131AL | 4" | 415/16 | 1 |
| 132-TB | — | 4½" | 51/16 | 13/64 |
| 133-TB | 133AL | 5" | 6 | 13/16 |
| 134-TB | 134AL | 6" | 7¼ | 1¼ |

* Not UL Listed or CSA Certified

UL File No. E-23018


** Not CSA Certified

CSA File No. 2884

Available with DURA-PLATE® Finish.

Perfect threads for easy thread-on!

Plastic Insulating Bushings



- Impact-resistant plastic insulation
- Ribbed for easy, secure gripping
- UL Listed 105° C



| CAT. NO. | SIZE | DIMENSIONS (IN.) | |
|----------|------|------------------|-------|
| | | A | B |
| 222-TB | ½" | 11/16 | 3/8 |
| 223-TB | ¾" | 13/32 | 13/32 |
| 224 | 1" | 13/16 | 9/16 |
| 225-TB | 1¼" | 129/32 | 9/16 |
| 226 | 1½" | 21/32 | 9/16 |
| 227 | 2" | 225/32 | 5/8 |
| 228-TB | 2½" | 33/8 | 3/4 |
| 229-TB | 3" | 41/16 | 3/4 |
| 230-TB | 3½" | 47/8 | 7/8 |
| 231 | 4" | 51/8 | 1 |
| 232 | 4½" | 511/16 | 1 |
| 233 | 5" | 63/16 | 1 |
| 234 | 6" | 77/16 | 1 |

UL Rated flame retardant 94V-1