

Fluorescent Lamps

Bulb Shape	Base	Watts	Nominal Length (in)	Order Code	Description	Case Qty	Rated Life (3 hr/ start)	Rated Life (12 hr/ start)	Initial Lumens	Mean Lumens	Color Temp K	CRI	High Color Rendering	Energy Savings	Reduced Wattage	Footnotes	Warning and Caution Notices	Additional Information
T12 Lamps (continued)																		
T12 High Output (800mA) Rapid Start Recessed Double Contact (continued)																		
6' High Output																		
T12	Recessed Double Contact (R17d)	85	72.0	15343	F72T12/SP30/HO 15PK	15	12000		6650	5990	3000	70					101	
		85	72.0	15347	F72T12/SP35/HO 15PK	15	12000		6650	5990	3500	73					101	
		85	72.0	15348	F72T12/SP41/HO 15PK	15	12000		6650	5990	4100	72					101	
		85	72.0	15137	F72T12/SPX30/HO 15PK	15	12000		6800	6120	3000	82	☞				101	
		85	72.0	15351	F72T12/SPX35/HO 15PK	15	12000		6800	6120	3500	82	☞				101	
		85	72.0	13697	F72T12/CW/HO 15PK	15	12000		6350	5520	4100	60					101	
		85	72.0	13699	F72T12/D/HO 15PK	15	12000		5350	4650	6500	75					101	Daylight
		85	72.0	12527	F72T12/N/HO	10	12000		4300	3610	3700	90	☞				101	Natural
		85	72.0	13701	F72T12/SGN/HO 15PK	15	12000		4900	4170	5400	82	☞				101	Sign White
85	72.0	13702	F72T12/WW/HO 15PK	15	12000		6550	5700	3000	52					101	Warm White		
7' High Output																		
T12	Recessed Double Contact (R17d)	100	84.0	13766	F84T12/CW/HO 15PK	15	12000		7700	6700	4100	60					101	
		100	84.0	13767	F84T12/D/HO 15PK	15	12000		6500	5660	6500	75					101	Daylight
		100	84.0	13768	F84T12/SGN/HO 15PK	15	12000		6000	5100	5400	82	☞				101	Sign White
8' High Output																		
T12	Recessed Double Contact (R17d)	110	96.0	13707	F96T12/C50/HO 15PK	15	12000		6750	5670	5000	90	☞				101	Chroma 50
		110	96.0	14653	F96T12/DX/HO	15	12000		6100	5185	6500	90	☞				101	Daylight Deluxe
8' High Output Watt-Miser® Energy Saving Lamps																		
T12	Recessed Double Contact (R17d)	95	96.0	66861	F96T12/HL30/HO/WM	15	12000		8850	7920	3000	77	☞	\$	↗	1	101	
		95	96.0	66862	F96T12/HL41/HO/WM	15	12000		8850	7920	4100	77	☞	\$	↗	1	101	
		95	96.0	66853	F96T12/HL41/HO/WM/UPC	15	12000		8850	7920	4100	77	☞	\$	↗	1	101	
T12 Very High Output (1500mA) Recessed Double Contact																		
T12	Recessed Double Contact (R17d)	110	48.0	10751	F48T12/CW/1500	24	10000		6200	4030	4100	60				4	101	
		165	72.0	13760	F72T12/CW/1500 15PK	15	10000		9000	6300	4100	60				4	101	
		185	96.0	13789	F96T12/CW/1500/WM 15PK	15	9000		12500	9380	4100	60		\$	↗	4	101	
		215	96.0	13781	F96T12/CW/1500 15PK	15	10000		13500	10125	4100	60				4	101	
		215	96.0	13783	F96T12/D/1500 15PK	15	10000		11500	8630	6500	74				4	101	Daylight
T12 Preheat																		
15"																		
T12	Medium Bi-Pin (G13)	14	15.0	10116	F14T12/CW	24	9000		650	550	4100	60					101	Preheat
		14	15.0	10117	F14T12/CW 6PK	24	9000		650	550	4100	60					101	Preheat
		14	15.0	22979	F14T12/K8 6PK	24	9000		700	650	3000	70					104	Preheat, Kitchen & Bath
18"																		
T12	Medium Bi-Pin (G13)	15	18.0	10183	F15T12/CW 6PK	24	9000		760	685	4100	60					101	Preheat
		15	18.0	22745	F15T12/K8 6PK	24	9000		785	730	3000	70					104	Preheat, Kitchen & Bath
		15	18.0	10185	F15T12/WW	24	9000		780	700	3000	52					101	Preheat
24"																		
T12	Medium Bi-Pin (G13)	20	24.0	80048	F20T12/SP35/ECO	24	9000		1275	1200	3500	73					101	Preheat
		20	24.0	15353	F20T12/SP41	24	9000		1275	1200	4100	72					101	Preheat
		20	24.0	80049	F20T12/SPX35/ECO	24	9000		1300	1220	3500	82	☞				101	Preheat
		20	24.0	80044	F20T12/C50/ECO	24	9000		875	790	5000	90	☞				101	Preheat
		20	24.0	80045	F20T12/CW/ECO	24	9000		1200	1150	4100	60					101	Preheat
		20	24.0	80046	F20T12/CW/ECO 6PK	24	9000		1200	1150	4100	60					101	Preheat
		20	24.0	80047	F20T12/D/ECO	24	9000		1025	945	6500	75					101	Preheat
		20	24.0	25575	F20T12/D/ECO/UPC	24	9000		1025	945	6500	75					101	Preheat, Daylight
		20	24.0	21325	F20T12/K8/ECO	24	9000		1275	1200	3000	70					104	Preheat, Kitchen & Bath
		20	24.0	14419	F20T12/SUN/ECO	24	9000		875	790	5000	90	☞				101	Preheat, Sunlight
		20	24.0	80050	F20T12/WW/ECO	24	9000		1250	1150	3000	52					101	Preheat, Warm White
		20	24.0	25577	F20T12/WW/ECO/UPC	24	9000		1250	1150	3000	52					101	Preheat, Warm White
Other Diameters																		
T6 Instant Start																		
T6	Single Pin (Fa8)	25	42.0	12221	F42T6/SP35	24	7500		1830	1700	3500	73					101	
		25	42.0	10720	F42T6/CW	24	7500		1750	1580	4100	60					101	
		25	42.0	10721	F42T6/WW	24	7500		1825	1640	3000	52					101	Warm White
		40	64.0	10805	F64T6/CW	24	7500		2800	2520	4100	60					101	
		40	64.0	10807	F64T6/WW	24	7500		2900	2610	3000	52					101	Warm White