

Features

Voltage Rating	240 Volt AC at 50/60 Hertz (UL)
Interrupting Rating	10 Kiloamp at 240 Volt AC Symmetrical (UL)
Poles	3 in
Current Rating	50 Amp at 40 Deg C
Wire Size	8 to 6 AWG (Copper), 8 to 4 AWG (Aluminum)
Terminal Type	LOAD LUG

Dimensions and Weight

Size	3 Inch Width x 3 Inch Depth x 3-3/4 Inch Height
------	---

Descriptions

Long Description	BOLT-ON CIRCUIT BREAKER, MOLDED CASE, THERMAL AND FIXED MAGNETIC TRIP, COMMON TRIP TYPE; 3 INCH WIDTH X 3 INCH DEPTH X 3-3/4 INCH HEIGHT SIZE; P1/P2/P3/P4/P5 PANEL BOARD USED ON; 8 TO 6 AWG (COPPER), 8 TO 4 AWG (ALUMINUM) WIRE SIZE
Commodity Description	3 POLE STANDARD TRIP BOLT-ON CIRCUIT BREAKERS
Additional Information	Frame Type BQ
Description	3P 50A 240V CB
Product Type	Bolt-On Circuit Breaker
extra long description	MOLDED CASE, THERMAL AND FIXED MAGNETIC TRIP, COMMON TRIP TYPE; 3 INCH W X 3 INCH D X 3-3/4 INCH H SIZE; P1/P2/P3/P4/P5 PANELBOARD USED ON; 8 TO 6 AWG (COPPER), 8 TO 4 AWG (ALUMINUM) WIRE SIZE; UL 489, CSA C22.2 APPROVAL; 240 VAC AT 50/60 HZ (UL) VOLTAGE RATING; BOLT-ON MOUNTING; 10 KILOAMP AT 240 VOLT AC SYMMETRICAL (UL) INTERRUPTING RATING; 50 AMPERE AT 40 DEG C CURRENT RATING; 3 POLE(S); LOAD LUG TERMINAL TYPE; SPEEDFAX , INSTA-WIRE BRAND; FRAME TYPE BQ; BQ MODEL

Manufacturer Information

Model	BQ
Brand	SIEMENS ELECTRICAL DISTRIBUTION PRODUCTS
Manufacturers Part Number	BQ3B050
GTIN	00783643102620
UPC	783643102620

Taxonomies, Classifications, and Categories

Type	Molded Case, Thermal and Fixed Magnetic Trip, Common Trip
------	---

Packaging

Weight per each	0.948
Carton	1

Uses, Certifications, and Standards

Mounting	Bolt-on
Used On	P1/P2/P3/P4/P5 Panel board
Approval	UL 489, CSA C22.2