INCLUDES

- (1) 11255VSR SDS-plus® Bulldog™ Xtreme 1 In. Rotary Hammer
- (1) Auxiliary Handle
- (1) Depth Gauge
- (1) Carrying Case

BENEFITS

Robust 8.0 Amp rotary hammer – delivers 2.0 Ft.-Lbs. of impact energy with three modes of ope

Vario-Lock positioning – rotates and locks chisel to optimize working angle

Variable-speed trigger with reversing – offers accurate bit starting

Integral clutch – disengages torque transmission if the bit gets into a bind-up scenario

Works with Bosch PRO+GUARD™ dust solutions – an end-to-end dust-collection system that h table 1 dust compliance

Multi-function selector – three modes of operation: rotary hammer, rotation only and hammer on

Bosch-exclusive rotating brush plate — provides equal power in forward and reverse

HammerHook – allows quick tool storage during the job

D-handle design – ideal for overhead and downward drilling applications

SDS-plus® bit system – tool-free bit changes with automatic bit locking

TECHNICAL DATA

Specifications

| Amperage | 8.0 |
|--------------|---------|
| Chuck Design | Keyless |
| Chuck Size | 1 in |
| | |

Drive System SDS-nlus

| Max. Hole Diameter in Wood | 3/4" - 1" |
|---------------------------------|--------------|
| No Load BPM | 0 - 5,800 |
| No Load RPM | 0-1,300 |
| Optimal Concrete Capacity Range | 3/16" - 5/8" |
| Rating | 120V |
| Voltage | 120V |
| Weight | 6.7lb |
| Weight (lbs.) | 6.7 |
| Width | 3.5" |