

Blackburn®

Service Wedge Clamps

T&B Catalog Number:



W40-1
78378633204
Active

UPC Number:

Status:

Description:

Aluminum Service Entrance Wedge Clamp and Slider for Wire Range: 4/0-2/0 ASCR, 4/0-2/0 AAAC, 4/0 Str.-2/0 Str. , Color Code Red

Features

Drop wire may be cut to exact length to adjust drop wire sag. This also saves the conductor.

Can be attached to bare neutral at any point in the span.

Versatile use. Flexible and rigid bails grip ACSR, AAC and AAAC conductors.

General

Style	W - Aluminum Service Wedge Clamp
Material	Aluminum
Conductor Range - ASCR	4/0-2/0
Conductor Range - AL	4/0 Str.-2/0 Str.
Conductor Range AAAC	4/0-2/0
Color Code	Red
Typical Tensile Values - Conductor	4/0 6/1 ACSR
Tensile Value (LB.)	1,900

Dimension Information

Length (inches)	12 3/4
D (inches)	2 3/8 flex.

Packaging

Package in Units	50
T&B Sold in UOM	Each
T&B Weight Per UOM	26.6 lbs. per 100

Notes

W40 series clamps rated 850 lb. Ultimate tension for 1/0 ASCR, AL or AAAC.

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com

Blackburn®

Service Wedge Clamps

T&B Catalog Number:



W40-1
78378633204
Active

UPC Number:

Status:

Description:

Aluminum Service Entrance Wedge Clamp and Slider for Wire Range: 4/0-2/0 ASCR, 4/0-2/0 AAAC, 4/0 Str.-2/0 Str. , Color Code Red

Features

Drop wire may be cut to exact length to adjust drop wire sag. This also saves the conductor.

Can be attached to bare neutral at any point in the span.

Versatile use. Flexible and rigid bails grip ACSR, AAC and AAAC conductors.

General

Style	W - Aluminum Service Wedge Clamp
Material	Aluminum
Conductor Range - ASCR	4/0-2/0
Conductor Range - AL	4/0 Str.-2/0 Str.
Conductor Range AAAC	4/0-2/0
Color Code	Red
Typical Tensile Values - Conductor	4/0 6/1 ACSR
Tensile Value (LB.)	1,900

Dimension Information

Length (inches)	12 3/4
D (inches)	2 3/8 flex.

Packaging

Package in Units	50
T&B Sold in UOM	Each
T&B Weight Per UOM	26.6 lbs. per 100

Notes

W40 series clamps rated 850 lb. Ultimate tension for 1/0 ASCR, AL or AAAC.

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com