Installation Accessories

Handles









				Not Type 3R	
NPT	Poly Handle	Cable Range	Nylon Handle	Neoprene Handle	Poly Handle w/Clamp & Bushing
1/2"	1PH12	.2082	FH111	-	-
3/4"	1PH34	.3288	-	31-111	-
1"	1PH1	.750875	-	-	1PM514
1 1/4"	1PH114	.875 - 1.000	-	-	1PM516
		1.000 - 1.125	-	-	1PM518
		1.125 - 1.250	-	-	1PM520
		1.250 - 1.375	-	-	1PM522

Notes: • Finger draw plates are recommended for easier connector closure on cord to cord assemblies.

• For available cord grips, see pgs 171-172.

Angles

Nylon 30° Angle	Metal 30° Angle	Metal Angle FS/FD Box 30°	Metal Straight Adapter
MP2	MA2	MAFS2*	MS2

* MAFS2 base measures approximately 4.2" x 2.7". Due to the variation in sizes of FS boxes, please verify that your FS box matches our dimensions, if not call Customer Service for other solutions.

Junction Boxes





NPT Guidelines

Cable Range	NPT	Cable Range	NPT
.312625	1/2"	.890 - 1.812	1 1/2"
.438812	3/4"	1.190 - 2.438	2"
.660 - 1.000	1"	2.062 - 2.438	2 1/2"
.875 - 1.375	1 1/4"		

NPT sizes are determined by the cable diameter and third party cord grip.

Male Inlet with Handle (Plug)

33-18075 + FH111

75 f) in³ 83.5 in **Order Example** Metal Box with Nylon Angle Poly 70°*[;] Vall Box Poly 70° Im Wall Box A typical order should include an inlet part number, a receptacle part number 1/2" MB312 31-1A053-080-12 MC212 51-BA058 59-BA058-12 AND the matching handles, angles or 31-1A053-080-34 3/4" MB334 MC234 51-BA058 59-BA058-34 other required accessories. 1" MB31 31-1A053-080-1 51-BA058 59-BA058-1 1 1/4" MB3114 31-1A053-080-114 51-BA058 59-BA058-114 _ 1 1/2' -59-BA058-112 ** 70° poly boxes are not drilled. Contact customer service if factory drilling is required. * For poly devices only.

* Interior volume with receptacle installed.

FDP2



Female Receptacle with Angle Adapter LP-843 see pg 167 33-14075 + MP2

* Recommended for cord to cord assembly applications, for easier connector closure. * Requires Padlockable Pawl option (-843) on receptacle.

31-1A226

** For watertight seal, the male inlet must also be ordered with the 'No Lockout Hole' option (-A155).

DS1PC

31-1A126

S

DS20