

# Insulated Metallic Grounding Bushings

## With Aluminum Lay-In Lug - Zinc Die Cast

### Features

- Tin plated aluminum alloy 6061-T6 rated for AL and CU conductor
- Liner is rated flame retardant to 105°C
- UL listed for use with copper or aluminum grounding conductor

### Applications


- Use to provide a means of grounding Rigid or IMC conduit
- Indoor or outdoor use (lay-in lug)
- Use with locknut to terminate service conduit to a cabinet
- Lug provided for bonding jumper to a neutral bus bar
- Round surface of bushing prevents damage to wire insulation
- Plastic liner prevents damage to wire insulation

### Standard Material

- Body - Zinc die cast
- Plastic insulator
- Lug - Aluminum
- Clamping screw - Steel
- Set screws - Steel



E195122



Catalog Number	UPC	Size	Grounding Lug Wire Size		Unit Carton	Ship Case	Weight/Case	Inches	
			Min.	Max.				A	B
<b>331</b>	13130	<b>1/2"</b>	14	4	50	500	30	1.04	.38
<b>332</b>	13140	<b>3/4"</b>	14	4	50	500	35	1.26	.41
<b>333</b>	13150	<b>1"</b>	14	4	25	250	23	1.53	.50
<b>334</b>	13160	<b>1-1/4"</b>	14	4	20	200	26	1.86	.53
<b>334A</b>	13170	<b>1-1/4"</b>	14	1/0	20	200	26	1.86	.53
<b>335</b>	13180	<b>1-1/2"</b>	14	4	10	100	16	2.13	.56
<b>335A</b>	13190	<b>1-1/2"</b>	14	1/0	10	100	16	2.13	.56
<b>336</b>	13200	<b>2"</b>	14	4	10	100	21	2.60	.66
<b>336A</b>	13210	<b>2"</b>	14	1/0	10	100	21	2.60	.66
<b>337</b>	13220	<b>2-1/2"</b>	14	1/0	---	50	20	3.15	.75
<b>337A</b>	13230	<b>2-1/2"</b>	6	250 MCM	---	50	20	3.15	.75
<b>338</b>	13240	<b>3"</b>	14	1/0	---	50	29	3.76	.75
<b>338A</b>	13250	<b>3"</b>	6	250 MCM	---	50	29	3.76	.75
<b>339</b>	13260	<b>3-1/2"</b>	14	1/0	---	10	15	4.27	.75
<b>339A</b>	13270	<b>3-1/2"</b>	6	250 MCM	---	10	15	4.27	.75
<b>340</b>	13280	<b>4"</b>	14	1/0	---	10	20	4.76	.75
<b>340A</b>	13290	<b>4"</b>	6	250 MCM	---	10	20	4.76	.75