

Fittings

INSTALLATION COMPONENTS

- | | | |
|--|---|---|
|  CI319 Face Plate Extension – for thick walls |  CI324 2" Hose Clamp |  326N Existing Home Inlet Kit |
|  CF328 Plaster Guard – for use with 329 Mounting Plate Existing Home Inlet Kit |  CF329 Inlet Mounting Plate |  CI330 Exhaust Vent |
|  CF361 Mounting Bracket with plaster guard |  CF361F Mounting Bracket with flanged spigot to assemble to any 382 series elbow |  CF362 90° Flanged ELL – standard |
|  CF363 90° Flanged ELL – special for 3" walls |  CF364 Flanged Tee |  CF365 Double-Flanged Tee |
|  CF366 Straight Flange |  CF367 Flexible Tubing – 2" ID. x 36" vinyl over steel wire, interwoven with nylon cord, can be cut to any length |  CF368 90° Street ELL |
|  CF369 45° Street ELL |  CF375 Utility Inlet – mounts on any flanged fitting; provides low-voltage contacts. Mounting box included. |  376 100' Wire 18/2 |
|  376UL 100' Wire 18/2 |  CF377 90° Sweep ELL-long |  376500 500' Wire 18/2 |
|  376500UL 500' Wire 18/2 |  CF380 Pipe Support with wire clip |  378 Nail Plate |
|  379 Solvent Cement |  CF382XS Short 90° ELL for installing VacPan™ where height is limited |  CF382 90° Sweep ELL |
|  CF382S 90° Sweep ELL for use with Model 329 only for narrow walls |  CF385 45° ELL |  CF383 90° Tee |
|  CF384 3-Way ELL |  CF388 Stop Coupling |  CF386 30° ELL |
|  CF387 45° Wye |  393 Metal Wall Cap – terminates exhaust discharge tube to outside |  CF389 End Cap |
|  392 Optional Muffler – reduces noise of currently installed power units |  CI398 Blank Cover Plate w/screws CI3981V (Ivory), CI398WH (White) |  394 Blank Cover Plate – white; used in place of wall inlet in speculative rough-in installations |
|  397 Wall Inlet Frame | |  399 Extension Sleeve for floor or thick wall installations |

METAL COMPONENTS – Zinc-coated/plated carbon steel for use in fire-walls to comply with fire codes.

- | | | |
|---|---|---|
|  300MTL Metal Tubing – 2" OD x 8', can be cut to size |  301MTL 90° ELL – Metal |  302MTL Slip Coupling |
|---|---|---|

CI3303RK Rough In – for 3-inlet installation includes:

- | | | |
|------------------------------|--------------------|-----------------------|
| 3 – Mounting Brackets | 1 – 90° Street ELL | 3 – 90° Tee Wyes |
| 3 – Plaster Guards | 1 – 45° Street ELL | 6 – Stop Couplings |
| 6 – Screws for Plaster Guard | 6 – Nail Guards | 1 – Solvent Cement |
| 3 – 90° Elbows | 6 – 90° Sweep ELLs | 1 – 1001 18/2 UL Wire |
| | 2 – 45° ELLs | |

CI3301RK Rough In – for 1-inlet installation includes:

- | | | |
|------------------------------|--------------------|--------------------|
| 1 – Mounting Bracket | 1 – 90° Elbow | 2 – 90° Sweep ELLs |
| 1 – Plaster Guard | 1 – 90° Street ELL | 1 – 45° ELL |
| 2 – Screws for Plaster Guard | 1 – 45° Street ELL | 1 – 90° Tee Wye |
| | 2 – Nail Guards | 2 – Stop Couplings |