

## 15 kV, 200A Loadbreak Elbow with Integral Seal



Ratings	
Description	15 kV
Minimum Partial Discharge	11
Max Rating Phase-to-Ground	8.3
Max Rating Phase-to-Phase	14.4
AC 60 Hz 1 Minute Withstand (rms)	34
DC 15 Minute Withstand	53
BIL and Full Wave (Crest)	95

## Production Tests:

- AC 1 Minute Withstand 34 kV
- Minimum Corona Level 11 kV (3pC)
- Test Point Voltage Test

Ratings	
Description	A rms
Continuous Current	200
Switching Current	200
Fault-closure Current for 0.17s after 10 Switching Operations	10,000 symmetrical
Short-time Current for 0.17s	10,000 symmetrical
Short-time Current for 3.00s	3,500 symmetrical

## 15 kV, 200A Loadbreak Elbow Size Reference Chart

Cable Size (AWG/kcmil)		Insulation Diameter	175 mil (100%) Insulation		220 mil (133%) Insulation	
STR/COMPR	COMPT/SOL	in (mm)	No Jacket Seal	Integral Jacket Seal	No Jacket Seal	Integral Jacket Seal
#2	#1	0.64-0.905 (16.2-23.0)	ELB-15-210B2	ELB-15-210B2-ES	ELB-15-210B2	ELB-15-210B2-ES
#1	1/0	0.64-0.905 (16.2-23.0)	ELB-15-210B1	ELB-15-210B1-ES	ELB-15-210B1	ELB-15-210B1-ES
1/0	2/0	0.64-0.905 (16.2-23.0)	ELB-15-210B10	ELB-15-210B10-ES	ELB-15-210B10	ELB-15-210B10-ES
2/0	3/0	0.64-0.905 (16.2-23.0)	ELB-15-210B20	ELB-15-210B20-ES	ELB-15-210C20	ELB-15-210C20-ES
3/0	4/0	0.83-1.06 (21.1-26.9)	ELB-15-210C30	ELB-15-210C30-ES	ELB-15-210C30	ELB-15-210C30-ES
4/0	250	0.83-1.06 (21.1-26.9)	ELB-15-210C40	ELB-15-210C40-ES	ELB-15-210C40	ELB-15-210C40-ES

## Related Test Report:

EDR-5574

## Elbow Kit Contents:

Elbow body  
 Copper top terminal  
 Loadbreak probe  
 Probe installation tool  
 Silicone lubricant  
 Sealing mastic (integral seal only)  
 Installation instructions sheet

## TE Technical Support Center

USA: +1 (800) 327-6996  
 Canada: +1 (905) 475-6222  
 Mexico: +52 (0) 55-1106-0800  
 Latin/S. America: +54 (0) 11-4733-2200  
 UK: +44 (0) 800-267666  
 France: +33 (0) 1-3420-8686  
 Netherlands: +31 (0) 73-6246-999  
 China: +86 (0) 400-820-6015

energy.te.com

© 2013 Tyco Electronics Corporation,  
 a TE Connectivity Ltd. Company. All Rights Reserved.

6-1773700-3 E480 02/2013  
 Raychem, TE Connectivity and TE connectivity (logo) are  
 trademarks. Other logos, product and/or company names  
 might be trademarks of their respective owners.



While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.