

## TRADITIONAL

### Traditional Combination Devices

Leviton's combination devices offer pleasing, practical designs that fit standard wallboxes. Switch/switch, switch/receptacle and switch/pilot light combinations are available. These devices come in a range of colors and are backed by a limited two-year warranty.

#### Sample Traditional Devices



#### Features and Benefits

- AC quiet switches have silver-cadmium oxide contacts and receptacles have double-wire contacts for maximum conductivity
- All devices have a grounding screw, except where noted
- Terminal screws accept up to #12 AWG copper or copper-clad wire
- Fit standard wallboxes
- Break-off tabs on devices with switches permit conversion to separate feeds
- Limited 2-year warranty

#### Tamper-Resistant Receptacles

- Shutter mechanism inside the receptacle blocks access to the contacts unless a two-prong plug is inserted, helping ensure hairpins, keys, etc., will be locked out
- TR symbol on residential receptacles assures they meet the NEC requirement
- Heavy-duty construction offers long, trouble-free service life

**Color Choices** Traditional combination devices are offered in a wide range of colors. To order colors, add suffix to Cat. No.



#### Related Products

Leviton carries a complete line of traditional switches. See page A-2 in the Switches & Motor Controls section for more information. Leviton carries a complete line of traditional receptacles. See page B-3 in the Straight Blade Devices section for more information.

**Traditional Combination Devices**

15A, 20A Combination Devices			
Rating	Switch: 15A-120VAC Receptacle: 15A-125V		Switch: 20A-120VAC Receptacle: 20A-125V
NEMA			
		5-15R	5-20R
Description	Color	Cat. No.	Cat. No.
Single Pole Switch/ Tamper-Resistant Receptacle*	White Ivory Light Almond Brown	T5225-W T5225-I T5225-T T5225	— — — —
Single Pole Switch/Receptacle*	White Ivory Light Almond Black Brown	5225-W 5225-I 5225-T — 5225	5335-W 5335-I — 5335-E 5335
Rating	15A-120/277VAC		20A-120/277VAC
Description	Color	Cat. No.	Cat. No.
Two Single Pole Switches, non-ground	White Ivory Brown	5224-W 5224-I 5224	— — —
Two Single Pole Switches*	White Ivory Light Almond Brown	5224-2W 5224-2I 5224-2T 5224-2	5334-W 5334-I — 5334
Rating	Switch: 15A-120VAC Pilot Light: 1/25W-125VAC		Switch: 20A-120VAC Pilot Light: 1/25W-125VAC
NEMA			
		5-15R	5-20R
Description	Color	Cat. No.	Cat. No.
Single Pole Switch/ Pilot Light*	White Ivory Light Almond Brown	5226-W 5226-I 5226-T 5226	— 5336-I — 5336
Rating	15A-120/277VAC		
Description	Color	Cat. No.	
3-Way Switch/Single Pole Switch*	White Ivory Light Almond Brown	5241-W 5241-I 5241-T 5241	
Two 3-Way Switches*	White Ivory Light Almond Brown	5243-W 5243-I 5243-T 5243	
Rating	Switch: 15A-120/277VAC Receptacle: 15A-125V		
Description	Color	Cat. No.	
3-Way Switch/ Receptacle*	White Ivory Brown	5245-W 5245-I 5245	



T5225-W



5224-W



5226-W



5241-I

\*With ground screw

Continued on next page