



R430011

Max Patrol Self Retracting Lifeline

FEATURES

- 11 foot working range
- 1 inch UHMWPE / polyester webbing with WebAlert™
- Thermoplastic housing
- Swivel top with steel carabiner included
- Aluminum rebar hook has a gate opening of 2 7/16 inches (63 mm)
- Steel form hook has a gate opening of 2 3/4 inches (70 mm)
- Snap hooks, rebar hooks, form hooks and carabiners are self-locking with a minimum tensile break strength of 5,000 pounds, and a 3,600 pound gate rating



MADE WITH
WebAlert™
INSPECTABLE WEBBING



SPECIFICATIONS

Model No.	Lifeline Connector	(A)	(B)	Aprox. Weight
R430011	Steel Snap hook	22 in (559 mm)	4 9/16 in (116 mm)	3.5lbs (1.59 kg)
R430011-R	Aluminum Rebar Hook	25 1/2 in (648 mm)	4 9/16 in (116 mm)	3.9 lbs (1.77 kg)
R430011-SR	Steel Form Hook	27 in (685 mm)	4 9/16 in (116 mm)	4.2 lbs (1.90 kg)

COMPLIANCE STANDARDS

Meets	Maximum Arrest Distance	Average Arrest Force	Maximum Arrest Force	Free Fall Limit	Capacity
ANSI Z359.14-2021 CLASS 1	24 in (610 mm)	900 lbf (4 kN)	1,350 lbs (6 kN)	24 in (610 mm)	130 - 310 lbs (59 - 141 kg)
OSHA 29 CFR 1910.140 & 1926.502	42 in (1,067 mm)	N/A	1,350 lbs (6 kN)	24 in (610 mm)	400 lbs (181 kg)

*See User Instructions for more information.

MAX PATROL™
Self Retracting Lifeline

⚠ WARNING: Compliant fall protection equipment must only be used as it was designed and adhere to the hierarchy of controls as discussed in ANSI Z359.2. Users MUST read and follow all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to heed these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

Technical Data Sheet