

**Class I, Groups A,B,C,D**  
**Class II, Groups E,F,G**  
**Class III**

## Reducing Bushings for Threaded RMC and IMC

### Applications

● RB reducing bushings are designed to reduce conduit hubs to a smaller size and are used in threaded rigid and IMC conduit systems.

### Features

● Smooth, rounded integral bushing protects conductor insulation.  
 ● Full, machined tapered threads (NPT).

### Standard Materials

● RB50-13 thru RB200-150: Steel.  
 ● RB250-100 thru RB600-500: Malleable Iron.  
 ● RB50-13A thru RB600-500A: Aluminum

### Standard Finishes

● Steel bushings: zinc electroplate.  
 ● Malleable iron bushings: zinc electroplate, dichromate and epoxy powder coating.  
 ● Aluminum bushings: natural finish.

### Compliances

● UL Standards 514B and 886.  
 ● CSA Standard C22.2 No. 18, C22.2 No. 30-M1986.



Catalog Number	Size (In.)	Catalog Number	Size (In.)
<b>Steel</b>		<b>Aluminum</b>	
RB50-13*	1/2 - 1/8	RB50-13A*	1/2 - 1/8
RB50-25*	1/2 - 1/4	RB50-25A*	1/2 - 1/4
RB50-38*	1/2 - 3/8	RB50-38A*	1/2 - 3/8
RB75-50	3/4 - 1/2	RB75-50A	3/4 - 1/2
RB100-50	1 - 1/2	RB100-50A	1 - 1/2
RB100-75	1 - 3/4	RB100-75A	1 - 3/4
RB125-50	1-1/4 - 1/2	RB125-50A	1-1/4 - 1/2
RB125-75	1-1/4 - 3/4	RB125-75A	1-1/4 - 3/4
RB125-100	1-1/4 - 1	RB125-100A	1-1/4 - 1
RB150-50	1-1/2 - 1/2	RB150-50A	1-1/2 - 1/2
RB150-75	1-1/2 - 3/4	RB150-75A	1-1/2 - 3/4
RB150-100	1-1/2 - 1	RB150-100A	1-1/2 - 1
RB150-125	1-1/2 - 1-1/4	RB150-125A	1-1/2 - 1-1/4
RB200-50	2 - 1/2	RB200-50A	2 - 1/2
RB200-75	2 - 3/4	RB200-75A	2 - 3/4
RB200-100	2 - 1	RB200-100A	2 - 1
RB200-125	2 - 1-1/4	RB200-125A	2 - 1-1/4
RB200-150	2 - 1-1/2	RB200-150A	2 - 1-1/2
<b>Malleable Iron</b>		<b>Aluminum</b>	
RB250-100	2-1/2 - 1	RB250-100A	2-1/2 - 1
RB250-125	2-1/2 - 1-1/4	RB250-125A	2-1/2 - 1-1/4
RB250-150	2-1/2 - 1-1/2	RB250-150A	2-1/2 - 1-1/2
RB250-200	2-1/2 - 2	RB250-200A	2-1/2 - 2
RB300-100	3 - 1	RB300-100A	3 - 1
RB300-125	3 - 1-1/4	RB300-125A	3 - 1-1/4
RB300-150	3 - 1-1/2	RB300-150A	3 - 1-1/2
RB300-200	3 - 2	RB300-200A	3 - 2
RB300-250	3 - 2-1/2	RB300-250A	3 - 2-1/2
RB350-200	3-1/2 - 2	RB350-200A	3-1/2 - 2
RB350-250	3-1/2 - 2-1/2	RB350-250A	3-1/2 - 2-1/2
RB350-300	3-1/2 - 3	RB350-300A	3-1/2 - 3
RB400-200	4 - 2	RB400-200A	4 - 2
RB400-250	4 - 2-1/2	RB400-250A	4 - 2-1/2
RB400-300	4 - 3	RB400-300A	4 - 3
RB400-350	4 - 3-1/2	RB400-350A	4 - 3-1/2
RB500-350†	5 - 3-1/2	RB500-350A†	5 - 3-1/2
RB500-400†	5 - 4	RB500-400A†	5 - 4
RB600-400†	6 - 4	RB600-400A†	6 - 4
RB600-500†	6 - 5	RB600-500A†	6 - 5

Shaded area indicates items suitable for Class I, Group A in addition to Class I, Groups B,C,D; Class II, Groups E,F,G and Class III.  
 † Class I, Groups C,D; Class II, E,F,G; Class III. \* Not UL Listed,