



Representative Image

Catalog No. TM2415C42

Description: 150AMCB LC 24-42CRT N1 22K COMB

UPC No 783164402858

Home > Load Centers > Load Centers

PowerMark Gold main breaker load centers arrive with a main breaker installed for a convenient and swift install. Main breakers allow for the user to stop the flow of electricity in the load center, shutting off all the power in the residence. The TM2415C42 features a full 42 circuit panel, a 150 A bus ampere rating, a copper bus, and a combination surface/flush enclosure.

Descriptors

Category	Load Centers
GO Schedule	RD

Specifications

Load Center Type	Standard
Input/Output Voltage	120/240V ac
Interrupting Capacity Rating	22
Amperage	150 A
Device type	Main Breaker
Enclosure	Indoor
Phase	1 Phase
1" Space	24
1/2" Space	36
Feed	Either
Door	Yes
GSA Compliance	No
Circuit Breaker Style	Plug-In
NEMA Rating	NEMA 1
Factory Installed Ground Kit	No

Classifications

UL/CUL Listing	UL
----------------	----



Publications

Title	Publication No.	Publication Type
Section 1 BuyLog: Load centers and circuit breakers Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line. Indoor Load Center	DET1023	Application and Technical
1 page outline drawing in pdf format.	10103091-SH20	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.