


## Set Screw LR Conduit Bodies



### Use:

Conduit bodies are used to gain access to the interior of a raceway for wire pulling, inspection and maintenance where the raceway changes direction. Assembled with Cover and Gasket.

- Assembled with Cover and Gasket.

### Materials:

- Aluminum Die-Cast
- Stamped Aluminum Cover and Neoprene Gasket


### Certification:



### Standards:

UL 514B  
CSA C22.2 No. 18  
NEMA FB-1  
NEC Article 348

## Set Screw LL Conduit Bodies



### Use:

Conduit bodies are used to gain access to the interior of a raceway for wire pulling, inspection and maintenance where the raceway changes direction. Assembled with Cover and Gasket.

- Assembled with Cover and Gasket.

### Materials:

- Aluminum Die-Cast
- Stamped Aluminum Cover and Neoprene Gasket

### Certification:



### Standards:

UL 514B  
CSA C22.2 No. 18  
NEMA FB-1  
NEC Article 348

## EMT (THINWALL) CONDUIT

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Pcs/ Unit	Ctn/Case Qty/Qty	Case Wt.
			A	B	C			

### Boxed

D100-CGV	15600-6	1/2"	4.30	1.30	2.40	-	27	7
D101-CGV	15606-8	3/4"	5.00	1.50	2.60	-	15	7.5
D102-CGV	15612-9	1"	5.80	1.80	2.90	-	14	9
D103-CGV	15618-1	1 1/4"	7.80	2.50	3.70	-	4	5.5
D104-CGV	15624-2	1 1/2"	7.80	2.50	3.90	-	4	6
D105-CGV	15630-3	2"	9.80	3.20	4.70	-	2	4.5
16-CG	15775-1	2 1/2"	10.50	4.40	5.60	-	1	5.6
17-CG	15776-8	3"	10.50	4.50	6.00	-	1	6.5
18-CG	15777-5	3 1/2"	15.47	5.43	7.36	-	1	8.5
19-CG	15778-2	4"	15.47	5.43	7.36	-	1	8.6

\* "D" bodies are also threaded for rigid

## EMT (THINWALL) CONDUIT

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Pcs/ Unit	Ctn/Case Qty/Qty	Case Wt.
			A	B	C			

### Boxed

D200-CGV	15636-5	1/2"	4.30	1.30	2.40	-	27	7
D201-CGV	15642-6	3/4"	5.00	1.50	2.60	-	15	7.5
D202-CGV	15648-8	1"	5.80	1.80	2.90	-	14	9
D203-CGV	15654-9	1 1/4"	7.80	2.50	3.70	-	4	5.5
D204-CGV	15660-0	1 1/2"	7.80	2.50	3.90	-	4	6
D205-CGV	15666-2	2"	9.80	3.20	4.70	-	2	5.5
26-CG	15779-9	2 1/2"	10.50	4.40	5.60	-	1	5.6
27-CG	15780-0	3"	10.50	4.50	6.00	-	1	6.5
28-CG	15781-2	3 1/2"	15.47	5.43	7.36	-	1	8.5
29-CG	15782-9	4"	15.47	5.43	7.36	-	1	8.6

\* "D" bodies are also threaded for rigid

EMT (THINWALL) CONDUIT