

Weatherproof Receptacle Covers

Flexi-Guard Weatherproof Plastic While-In-Use Covers

Intermatic's weatherproof covers are easy to install, offer flexible options and reduce the amount of inventory needed to cover the project.

Features:

- Complies with 2008 NEC Article 406.8 (B)
- Packaged with 3 patented inserts for GFCI, duplex, toggle or round receptacles
- Two-gang models include 6 snap-together, rotating inserts that create 70 combinations to fit almost every application. See page 93 for insert options
- Single-gang covers mount both vertically and horizontally by switching the hinge points
- Clear or white cover
- Heavy-duty polycarbonate construction
- Inserts include keyhole slots for up to 14 installation configurations
- Pre-adhered gasket
- Meets requirements for cold impact testing at -60° F (-51°C)
- Lockable hasp for .250 in. (6.35 mm) shank lock — WP1100C and WP1100WC only
- Lockable hasp for .125 in. (3.175 mm) shank lock — WP3100C and WP3103C only
- Hidden hinges — WP3100C and WP3103 only
- Easy to remove cord set exit ports — WP3100C and WP3103 only
- Max cord size for all covers: (2) 14 gauge AWG OR (1) 12 gauge AWG
Except WP1250C and WP1150C: (2) 14 gauge AWG OR (1) 10 gauge AWG

Warranty: Limited 1-year warranty

Model	Description	Depth (in.)	Color	Cord Diam. (in.)	Exit Port Length (in.)
WP1100WC	Single-gang Vertical or Horizontal w/(WP17) Flexi-Guard Inserts	2¾	White	0.5	0.75
WP1110C	Single-gang Vertical or Horizontal w/(WP17) Flexi-Guard Inserts	3⅝	Clear	0.5	0.75
WP1150C	Single-gang Vertical or Horizontal w/(WP17) Flexi-Guard Inserts	4¾	Clear	0.8	1.27
WP1220C	Two-gang with (WP217) Flexi-Guard Inserts	2¼	Clear	0.5	0.75
WP1230C	Two-gang with (WP217) Flexi-Guard Inserts	3⅛	Clear	0.5	0.75
WP1250C	Two-gang with (WP217) Flexi-Guard Inserts	4¾	Clear	0.8	1.27
WP3100C	Single-gang Vertical or Horizontal w/(WP17) Flexi-Guard Inserts	2¾	Clear	0.5	0.97
WP3103C	3/0 Adapter Plate for 3 in. Round Box Applications				
	Single-gang Vertical or Horizontal w/(WP17) Flexi-Guard Inserts	2¾	Clear	0.5	0.97

Note: See page 93 for insert information.



1.00 lbs
0.45 kg



**NEW
PRODUCT**

Weatherproof