

15 Amp Wetguard Straight Blade & Locking Devices

2-Pole, 2-Wire • 2-Pole, 3-Wire

Amp	Volt	NEMA Configuration	Plug IP69K	Plug Cap	Connector IP69K	Connector Cap	Single Outlet	Duplex Outlet	Single Inlet	Connector for Single Inlet	Single Receptacle	Receptacle Cover with Gasket
Straight Blade 2-Pole, 2-Wire Devices												
15	125	1-15		14W04	14W*	15W04	50W50*	90W04-S	80W04-D	59W04	79W04-C	—
Locking 2-Pole, 2-Wire Devices												
15	125	L1-15		24W04	14W*	25W04	50W50*	95W04-S	85W04-D	64W04	74W04-C	—
Straight Blade 2-Pole, 3-Wire Devices												
15	125	5-15		14W47* ‡	14W*	15W47* ‡	50W50*	90W47-S	80W47-D	59W47	79W47-C	5261-CR 60W03*
15	250	6-15		14W49	14W*	15W49	50W50*	90W49-S	80W49-D	59W49	79W49-C	5661-CR 60W03*
15	277	7-15		14W34	14W*	15W34	50W50*	—	—	—	—	—
15	347	24-15		14W15	—	15W16	50W50*	—	—	—	—	—
Locking 2-Pole, 3-Wire Devices												
15	125	L5-15		24W47* ‡	14W*	25W47* ‡	50W50*	95W47-S	85W47-D	64W47	74W47-C	47CM-10 60W03*
15	250	L6-15		24W49	14W*	25W49	50W50*	95W49-S	85W49-D	64W49	74W49-C	45CM-60 60W03*
15	277	L7-15		24W34	14W*	25W34	50W50*	95W34-S	85W34-D	64W34	74W34-C	47CM-60 60W03*

Plugs & Connectors need caps attached in order to achieve IP69K rating.
NEMA configuration diagrams represent plug blade configuration.

* Available in black. To order, add "–B" suffix to catalog number.
‡ Replacement interior available. To order, add "–IN" to catalog number (Ex: 14W47-IN).