

NMUA TYPE B NON-METALLIC HOSE UL LISTED AND CSA APPROVED

LFNC SEALTITE® NMUA (TYPE B)
NON-METALLIC FLEXIBLE CONDUIT



DESCRIPTION

- Non-metallic Type B liquid tight conduit
- Designed for standard commercial and industrial applications
- Approved in US (per NEC) for direct burial applications
- Also available by special order in other colors (consult the factory)
- Uses special non-metallic connectors for easy installation
- Can also be used with a liquid tight connector
- Additional Put-ups available

COMMON NEC Articles

- 300.22 (C) Other Spaces Used for Environmental Air (Plenums)
- 501.10 (B) (2) Class I Div. 2; 502.10 (A) (2) and (B) (2) Class II Div. 1 & 2; 503.10 (A) (3) and (B) Class III Div. 1 & 2
- 356 Liquid tight Flexible Nonmetal Conduit (LFNC-B)

SPECIFICATIONS

- Co-extruded PVC conduit
- Color: Gray
- Temp. range: -17°F to +176°F (-27°C to +80°C)
- UV (sunlight) resistant
- Oil resistant
- UL Approved #E211327
- CSA Approved #20817

APPLICATIONS

- HVAC industry
- Commercial and industrial applications requiring UL and CSA approvals

See: www.ul.com www.csa-international.org
www.nfpa.org www.naed.org
www.nema.org www.anacondasealtite.com



Rigid PVC reinforced
3/8" - 2"



| Trade Size (mm) | Item ID | Std. Pkg. (feet) | Inside Diameter (inches) | | Outside Diameter (inches) | | Bend Radius (inches) | Weight (lbs/100 ft) |
|-----------------|---------|------------------|--------------------------|-------|---------------------------|--------|----------------------|---------------------|
| | | | Min | Max | Min | Max | | |
| 3/8" (12) | 39702 | 100 | 0.484 | 0.504 | 0.690 | 0.710 | 2.0 | 11 |
| | 39708 | 1000 | | | | | | |
| 1/2" (16) | 39712 | 100 | 0.622 | 0.640 | 0.820 | 0.840 | 3.3 | 15 |
| | 39713 | 1000 | | | | | | |
| 3/4" (21) | 39722 | 100 | 0.820 | 0.840 | 1.030 | 1.050 | 4.5 | 20 |
| | 39724 | 700 | | | | | | |
| 1" (27) | 39731 | 100 | 1.041 | 1.066 | 1.290 | 1.3150 | 6.5 | 27 |
| | 39734 | 500 | | | | | | |
| 1-1/4" (35) | 39741 | 50 | 1.380 | 1.410 | 1.630 | 1.660 | 8.0 | 36 |
| | 39742 | 100 | | | | | | |
| 1-1/2" (41) | 39753 | 50 | 1.575 | 1.600 | 1.865 | 1.900 | 9.0 | 45 |
| | 39752 | 100 | | | | | | |
| 2" (53) | 39761 | 50 | 2.020 | 2.045 | 2.340 | 2.375 | 11.1 | 67 |
| | 39768 | 100 | | | | | | |

FITTINGS FINDER



IP 65/66/67 with approved fittings