

DSN60 Switch-Rated Plugs & Receptacles – 60 A

UL/CSA Ratings

- **Max Amperage & Voltage**
60 A, 600 VAC
- **Switch-Rating (AC Only)**
Branch Circuit & Motor Circuit
Disconnect Switching
- **Horsepower Ratings**

| | | |
|-------|----|--------|
| 120 V | 1Ø | 2 hp |
| 240 V | 1Ø | 3 hp |
| 208 V | 3Ø | 7.5 hp |
| 240 V | 3Ø | 7.5 hp |
| 480 V | 3Ø | 20 hp |
| 600 V | 3Ø | 20 hp |
- **Short Circuit Rating**
100 kA Close & Withstand
Testing was performed with RK1
current limiting fuses sized at 400%
of the highest full load motor
ampacity associated with the
devices hp rating.
- **Environmental Ratings**
Type 4X/IP69/IP69K*
*Also meets IP66/IP67 requirements.
- **Temperature Range**
Min -40°F/Max 140°F
See pg 266 for temps below -15°F.
- **Wiring Capacity**
Min 14 AWG Max 4 AWG
Aux Contacts - Max 14 AWG
- **Certifications**
UL 2682, UL 1682, CSA 182.1

Receptacle (female)



Inlet (male)



! Don't forget to add installation accessories to your order

North American UL/CSA Configurations

| Voltage | Polarity | Part # Poly | Part # Poly |
|-----------|----------|----------------|----------------|
| 120 V | 1P+N+G | 63-64165 | 63-68165 |
| 120 208 V | 3P+N+G | 63-64167 | 63-68167 |
| 125 V | 1P+N+G | 63-64075 | 63-68075 |
| 125 250 V | 2P+N+G | 63-64076 | 63-68076 |
| 208 V | 2P+G | 63-64162 | 63-68162 |
| 208 V | 3P+G | 63-64163 | 63-68163 |
| 250 V | 2P+G | 63-64072 | 63-68072 |
| 250 V | 3P+G | 63-64073 | 63-68073 |
| 277 V | 1P+N+G | 63-64045 | 63-68045 |
| 277 480 V | 3P+N+G | 63-64047 | 63-68047 |
| 347 600 V | 3P+N+G | 63-64147 | 63-68147 |
| 480 V | 2P+G | 63-64042 | 63-68042 |
| 480 V | 3P+G | 63-64043 | 63-68043 |
| 600 V | 2P+G | 63-64142 | 63-68142 |
| 600 V | 3P+G | 63-64143 | 63-68143 |

For international configurations and ratings (IEC, CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.

Main Options



**Auxiliary/Pilot
Contacts**



**Mushroom
Pawl**



Padlock Pawl



**Closed Lid
Configuration**

Recommended for cord
applications to keep lid
tucked in to avoid damage.

Receptacle Options

Suffix

Inlet Options

Suffix

With 2 Auxiliary/Pilot Contacts

Recept # -972

With 2 Auxiliary/Pilot Contacts

Inlet # -972

With 3 Auxiliary/Pilot Contacts

Recept # -973

With 3 Auxiliary/Pilot Contacts

Inlet # -973

With 4 Auxiliary/Pilot Contacts

Recept # -974

With 4 Auxiliary/Pilot Contacts

Inlet # -974

Straight Insertion

Recept # -352~

Self-Ejecting Plug Release**

Inlet # -338

Self-Ejecting Connector Release**

Recept # -354~

With No Lockout Hole

Inlet # -A155

Mushroom Pawl

Recept # -375

For Auxiliary Switch

Inlet # -270

Padlock Pawl

Recept # -843

Notes: + Not UL/CSA listed.

Padlockable Mushroom Pawl

Recept # -375-843

** For self-ejecting connectors and plugs, a -443 suffix must be added to the handle part number. See pages 251-252 for more information.

Metal Pawl

Recept # -824

~ Standard closed lid configuration.

Closed Lid Configuration

Recept # -NC

With Auxiliary Switch

Recept # -270+



! See pages 243-252 for detailed information on these options

Order Example: 480 V DSN60 + 2 auxiliary contacts
DSN60 Inlet 3P+G = 63-68043-972


INSTALLATION ACCESSORIES – SIZE 3


Accessories can be used with either poly or metal plugs and receptacles.

HANDLES

| HANDLE w/NPT | | Part # Poly | Part # Metal |
|---|--------|-------------|--------------|
|  | 1/2" | 513P0N05 | 593P0N05 |
| | 3/4" | 513P0N07 | 593P0N07 |
|  | 1" | 513P0N10 | 593P0N10 |
| | 1 1/4" | 513P0N12 | 593P0N12 |

For available cord grips, see page 169. Add -443 for self-ejecting.


| POLY HANDLE w/CORD GRIP | Cable Range | Part # |
|---|---------------|----------|
|  | .520 - .680" | 713P0CP5 |
| | .680 - .980" | 713P0DP4 |
| | .980 - 1.260" | 713P0EP4 |

| METAL HANDLE w/CORD GRIP | Cable Range | Part # |
|---|----------------|----------|
|  | .625 - .750" | 793P0CS4 |
| | .750 - .875" | 793P0DS1 |
| | .875 - 1.000" | 793P0DS3 |
| | 1.000 - 1.125" | 793P0ES2 |


| POLY HANDLE | Cable Range | Part # |
|---|-------------|----------|
|  | .39 - 1.18" | 513P0D30 |

| POLY HANDLE w/BUILT IN DRAW GRIPS | Cable Range | Part # |
|--|-------------|-------------|
|  | .39 - 1.18" | 513P0D30473 |

Makes connector closures easier.


| POLY HANDLE w/CLAMP & BUSHING | Cable Range | Part # |
|---|----------------|----------|
|  | .750 - .875" | 713P0S14 |
| | .875 - 1.000" | 713P0S16 |
| | 1.000 - 1.125" | 713P0S18 |
| | 1.125 - 1.250" | 713P0S20 |
| | 1.250 - 1.375" | 713P0S22 |

ANGLES


| POLY ANGLE | | |
|---|-----|-------|
|  | 30° | 513M3 |

| | | |
|---|-----|-------|
|  | 70° | 513M7 |
|---|-----|-------|

Panel mounting only.

| METAL ANGLE | | |
|---|----|-------|
|  | 0° | 593M0 |

| | | |
|---|-----|-------|
|  | 30° | 593M3 |
|---|-----|-------|

| | | |
|---|---------------|---------|
|  | FS/FD Box 30° | 793M3FS |
|---|---------------|---------|

* Base measures approximately 4.2" x 2.7". Due to the variation in sizes of FS boxes, please verify that your FS box matches our dimensions, if not call Customer Service for other solutions.

| | | |
|---|-----|-------|
|  | 70° | 593M7 |
|---|-----|-------|

BOXES

| POLY CONDUIT ENTRY w/NPT | | | Part # |
|---|-----|------|----------|
|  | 30° | 1/2" | 513B3N05 |
| | 30° | 3/4" | 513B3N07 |
| | 30° | 1" | 513B3N10 |


* 13.5 in³

* Interior volume with receptacle installed.


| POLY WALL BOX w/ANGLE | | | Part # |
|---|-----|--|----------|
|  | 70° | | 513C7000 |

* 179.41 in³

70° poly boxes are not drilled. Contact Customer Service if factory drilled is required.


| | | |
|---|------------|---------|
|  | Ground Bar | 51AA089 |
|---|------------|---------|


* Interior volume with receptacle installed.

| POLY ANGLE WITH METAL BOX w/NPT | | | Part # |
|---|-----|--------|----------|
|  | 70° | 1/2" | 713C7N05 |
| | 70° | 3/4" | 713C7N07 |
| | 70° | 1" | 713C7N10 |
| | 70° | 1 1/4" | 713C7N12 |
| | 70° | 1 1/2" | 713C7N15 |

* 177.7 in³

* Interior volume with receptacle installed.

| METAL BOX w/NPT | | | Part # |
|--|----|--------|----------|
|  | 0° | 1/2" | 7T1F0N05 |
| | 0° | 3/4" | 7T1F0N07 |
| | 0° | 1" | 7T1F0N10 |
| | 0° | 1 1/4" | 7T1F0N12 |


| POLY ANGLE WITH METAL BOX w/NPT | | | Part # |
|---|-----|--------|----------|
|  | 30° | 1/2" | 713C3N05 |
| | 30° | 3/4" | 713C3N07 |
| | 30° | 1" | 713C3N10 |
| | 30° | 1 1/4" | 713C3N12 |

* 29.6 in³


* Interior volume with receptacle installed.

NPT on top or bottom (if rotated). For other NPT configurations, contact Customer Service.

MISCELLANEOUS ACCESSORIES


| FINGER DRAWPLATES | | |
|---|----------|---|
|  | 61-6A346 | Set of Two (2) Recommended for cord to cord assembly applications, for easier connector closure. |

| PROTECTIVE INLET/PLUG CAP | | |
|---|----------|------------------------|
|  | 61-6A426 | For Inlets/Plugs Only. |

| PADLOCKABLE INLET/PLUG CAP | | |
|---|----------|------------------------|
|  | 61-6A826 | For Inlets/Plugs Only. |

| SPRING-LOADED PADLOCKABLE INLET/PLUG CAP | | |
|---|----------|---|
|  | 61-6A226 | Metal – For Inlets/Plugs Only. -A155 suffix required to maintain water ingress protection. |

| CORD GRIP with or w/o MESH | | |
|---|------------|--|
|  | see pg 169 | |

| RECEPTACLE LOCKING PIN | | |
|---|--------|--|
|  | LP-843 | Requires Padlockable Pawl option (-843) on receptacle. |