Dimmer model numbers

Preset dimmers

Single-pole	AY-600P- CC 3
120V 600W	
Single-pole	AY-10P- <u>CC</u> 3
120V 1000W	
3-way	AY-603P- CC ³
120V 600W	
3-way	AY-103P- <u>CC</u> 3
120V 1000W	

Preset dimmers with locator light

Single-pole	AY-600PNL- CC ³
120V 600W	
Single-pole	AY-10PNL- CC 3
1000W	
3-way	AY-603PNL- CC 3
120V 600W	
3-way	AY-103PNL- <u>CC</u> 3
120V 1000W	

eco-dim_® preset dimmer

3-way/single-pole	AY-603PG- EE 2
120V 600W	

eco-dim model guarantees at least 15% energy savings compared to a standard switch.

▽ Magnetic low-voltage dimmers

Preset dimmers

Single-pole	AYLV-600P- CC ³
120V 600VA (450W)	
3-way	AYLV-603P- CC ³
120V 600VA (450W)	

The stated VA (Volt-Ampere) rating includes the magnetic transformer heat losses and the lamp load. The stated W (Watt) rating is the maximum lamp wattage based on assumed 20% transformer loss.

<u>CC</u>³: Gloss color codes, see pg. 125

EE²: Available in White (WH), Ivory (IV), Almond (AL) and Light Almond (LA)

(Wallplates not included, order separately, see pg. 168)

Dimmer, fan and fan/light control model numbers

Z 3-wire fluorescent dimmers*

Preset dimmers

3-way/single-pole	AYF-103P- <u>CC</u> 3
120V 8A 3-way/single-pole	AYF-103P-277- CC ³
277 V 6 A	ATT-1001-211- <u>00</u>

For use with Hi-lume_®, Hi-lume_® Compact SE, Hi-lume_® 3D, Eco-10_®, EcoSystem_® ballasts.

Also compatible with Hi-lume_® LED driver.

No derating required if ganged.

Adjustable low-end trim.

Hi-lume LED drivers: 3-wire fluorescent dimmers*

Preset dimmers

3-way/single-pole	AYF-103P- CC 3
120V 8A	
3-way/single-pole	AYF-103P-277- CC 3
277V 6A	

For use with Hi-lume LED driver only.

For more information on Hi-lume LED drivers,

visit www.lutron.com/HilumeLED.

No derating required if ganged. Adjustable low-end trim.

⊯Fan control

Fan control—quiet 3-speed

3-way/single-pole	
120V 1.5A	AYFSQ-F- <u>CC</u> 3

★ Fan/light control

Fan control and dimmer—quiet 3-speed

Single-pole fan control	AY2-LFSQ- <u>CC</u> 3
120V 1.5A (left)	
Single-pole dimmer 120V 300W	
incandescent/halogen (right)	

All models must be derated if ganged unless otherwise noted, see pg. 170. For more information on ballasts, visit www.lutron.com/ballasts.

*Requires neutral wire connection.