

MB10/22.SF

ABB contact for United
States of America



General Information

Extended Product Type:	MB10/22.SF
Product ID:	1SNA116302R2300
EAN:	3472591163025
Catalog Description:	MB10/22.SF Screw Clamp Terminal Blocks - For 10.3 x 38 fuses - Grey
Long Description:	MB10/22.SF Screw Clamp Terminal Blocks Fuse

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Screw Clamp Terminal Blocks

Ordering

EAN:	3472591163025
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85361050

Dimensions

Product Net Width:	22.0 mm
Product Net Height:	89.5 mm
Product Net Depth:	67.0 mm
Product Net Weight:	83.00 g

Container Information

Package Level 1 Units:	10 piece
Package Level 1 Width:	176 mm
Package Level 1 Height:	75 mm
Package Level 1 Length:	200 mm
Package Level 1 Gross Weight:	0.83000 kg
Package Level 1 EAN:	3472591163025
Package Level 2 Units:	100 piece
Package Level 2 Width:	300 mm
Package Level 2 Height:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Gross Weight:	8.8 kg
Package Level 3 Units:	2400 piece
Product Packing Type:	Box

Environmental

Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C
RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007-01-01

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Connecting Capacity-Main Circuit UL/CSA:	Screw Clamp / Rigid 1x 18 ... 6 AWG

Flammability According to UL94: V0

Additional Information

Ambient Temperature:	-5 ... +40 °C
Color:	Grey
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.5 ... 6 mm ² Screw Clamp / Rigid 1x 0.5 ... 10 mm ²
Connection Type:	Screw clamp
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Function:	Fuse
IIT Publishing Status:	Level 0 - Information enabled
Insulation Material:	Polyamide
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Number of Levels:	1
Product Main Type:	MB10/22.SF
Product Name:	Terminal Block
Rated Cross-Section:	6 mm ²
Rated Current (I_n):	Main Circuit 30 A
Rated Voltage (U_r):	800 V
Recommended Screw Driver:	6.5 mm
Spacing:	22 mm
Sub-Function:	For 10.3x38 Fuses
Sub-Function 2:	Without fusion indicator
Wire Stripping Length:	12.5 mm

Certificates and Declarations (Document Number)

cUL Certificate:	1SND161000A0202
Declaration of Conformity - CE:	1SND225007C1006
GOST Certificate:	1SND161005A1104
RoHS Information:	1SND230023F0201

Classifications

ETIM 4.0:	EC000899 - Fuse terminal block
ETIM 5.0:	EC000899 - Fuse terminal block
Object Classification Code:	X

