


Components – CR460 Series Lighting Contactors

Basic Contactor



Combined with other appropriate components, basic contactors allow configuration into any available electrically or mechanically held model. Includes two power poles.


Description	Cat. No.	List Price, GO-10MB
Base with 1NO-1NC	CR463L11A*A	\$165.00
Base with 2NO	CR463L20A*A	160.00

Coil Voltage

Replace * in base catalog number with appropriate coil digit from the table below. There is no price adder for coil selection.

	Coil Voltage		Coil Digit
	AC, 60 Hz	AC, 50 Hz	
Suitable for electrically or mechanically held contactors	24V	20V	C
	28V	24V	D
	115-120V	110V	J
	200-208V	—	L
	230-240V	220V	S
Suitable for electrically held contactors. CPT required when used with mechanically held contactors	277V	240V	N
	347V	—	T
	460-480V	440V	U
	575-600V	550V	Y

Power Poles



CR460 Series basic contactors accept up to 6 single- or double-pole power poles.

These can be used to form up to:

- 12 NO poles when 6 double-poles are used in the NO positions (1-6) *or*
- 8 NC poles with 4 double-poles in the NC positions (1-4) + 4 NO poles with 2 double-poles in the 2 NO positions (5-6)

Power Poles	Cat. No.	List Price, GO-10MB
Single Pole	CR460XP31	\$43.00
Double Pole	CR460XP32	82.00

Packaged individually and overpacked in multiple of 5.

Conversion Kits for Mechanically Held Contactors



Kits for converting electrically held contactors to a mechanically held version. Kits include control module, latch, latch cover and auxiliary contacts plus installation instructions. Conversion kits are suitable for coil voltages 277V and below. Use CPT to

reduce coil voltage if line voltage is higher than 277V (see Fuse and Transformer Kits table on page 7 for CPT selection).

Coil Volts	Control	Control Volts	Cat. No.	List Price, GO-10MB
24-277Vac	2-wire	24 Vac	CR460XMB	\$105.00
		110-120 Vac	CR460XMC	105.00
		200-277 Vac	CR460XMD	105.00
		12-24 Vdc	CR460XME	105.00
	3-wire	24 Vac	CR460XMM	115.00
		110-120 Vac	CR460XMN	115.00
		200-277 Vac	CR460XMP	115.00
		12-24 Vdc	CR460XMR	115.00

Auxiliary Contacts



Each contactor may use one single or one double auxiliary contact block on each side of the base.

When installed on the left side the contacts are NO, when installed on the right side the contacts are NC. This allows a total of 2NO + 2NC contacts maximum. See Additional Auxiliary Contacts tables on pages 11 and 13 for contacts data.

Auxiliary Block	Cat. No.	List Price, GO-10MB
Single Pole	CR460XB1	\$9.00
Double Pole	CR460XB2	17.00

Enclosure Kits

See pages 17-18 for enclosure dimensions.

Enclosure Type	With no CPT or pilot device		With provision for CPT and/or pilot device	
	Cat. No.	List Price, GO-10 MB	Cat. No.	List Price, GO-10 MB
1	CR460XE1B	\$43.00	CR460XE1D	\$83.00
Type 1, Flush Mount	CR460XE8B	80.00	—	—
12/3R	CR460XE2B	100.00	CR460XE2D	140.00
4	—	—	CR460XE4D	235.00