



# Compact Series Camera Reels Compact2, C40 and M40



**RIDGID® SeeSnake® Compact series camera reels deliver big performance in a small package. Choose from three models to handle a wide range of demanding inspections. Compatible with the new SeeSnake CS6x Versa digital reporting monitor for fast set-up and easy viewing, while built-in Wi-Fi and Bluetooth make live streaming and inspection to an iOS™ or Android™ device simple with the free HQx Live app.**

- 25 mm self-leveling camera head provides a crisp image that is always upright
- TruSense™ technology features two-way communication between the camera and a CSx series Wi-Fi enabled monitor\*
- High dynamic range image sensor provides bright, saturated images with improved detail, even in difficult lighting conditions\*
- TiltSense inclinometer lets you know camera's degree of tilt inside the pipe when used with a CSx series monitor\*
- Equipped with high power FleXmitter® 512 Hz sonde which is compatible with all RIDGID locators
- Download the free HQx Live app to view and record inspection jobs on your phone or tablet
- Use with the SeeSnake CS6x Versa to create the optimal viewing angle and for fast, efficient job setup







## SPECIFICATIONS

- Light Source ..... High-Intensity LED
- Push Cable Length..... 100' (30 m)/131' (40 m)
- Push Cable Minimum Bend Radius.....2.5" (64 mm)
- 512 Hz Sonde ..... High-power Flexmitter®
- Dimensions (LxWxH).....25" x 14" x 17"  
(626 mm x 360 mm x 429 mm)
- Operating Temperature ..... 14°F to 122°F (-10°C to 50°C)
- Storage Temperature..... 14°F to 158°F (-10°C to 70°C)
- Ingress Protection (without Monitor).....IPx6

## COMPACT SERIES QUICK COMPARISON GUIDE

CAMERA REEL	CAMERA HEAD	PUSH CABLE	MINIMUM BEND RADIUS	LINE CAPACITY
Compact2 Camera Reel	25 mm (1") Self-Leveling	100' (30 m)	2.5" (64 mm)	1.5" - 6" (38 mm - 152 mm)
Compact C40 Camera Reel	 25 mm (1") Self-Leveling w/TruSense Technology	131' (40 m)	2.5" (64 mm)	1.5" - 6" (38 mm - 152 mm)
Compact M40 Camera Reel	 25 mm (1") Self-Leveling w/TruSense Technology	131' (40 m)	3" (76 mm)	1.5" - 8" (38 mm - 203 mm)

## ORDER INFORMATION

CATALOG NO.	DESCRIPTION	WEIGHT	
		(lb.)	(kg)
48093	Compact2 (Reel Only)	17.0	7.7
65098	Compact2 w/CS6x Versa Monitor	21.9	9.9
65103	Compact2 w/CS6x Versa Monitor, Battery and Charger	24.9	11.3
63668	Compact C40 (Reel Only)	17.2	7.8
63823	Compact C40 w/CS6x Versa Monitor	22.1	10.0
63828	Compact C40 w/CS6x Versa Monitor, Battery and Charger	25.1	11.4
63673	Compact M40 (Reel Only)	22.0	9.8
63813	Compact M40 w/CS6x Versa Monitor	26.9	12.0
63818	Compact M40 w/CS6x Versa Monitor, Battery and Charger	29.9	13.6

## ACCESSORIES

CATALOG NO.	DESCRIPTION
47793	36 mm Pipe Guide, 25 mm Camera, Pkg of 1
35338	45 mm Pipe Guide, 25 mm Camera, Pkg of 2
97462	60 mm Pipe Guide, 25 mm Camera, Pkg of 6
46708	85 mm Pipe Guide, 25 mm Camera, Pkg of 2
46713	125 mm Pipe Guide, 25 mm Camera, Pkg of 2
63868	Various Pipe Guides, 25 mm Camera Head
17553	Spanner Wrench, 25 mm



### HDR

High Dynamic Range (HDR) image sensor offers clear in-pipe imaging..



### TiltSense™

Data Sensor displays camera's angle in pipe.



Scan for more information on HQx Live

