

FEATURES

- HolsterTop® with Lock-In System secures tools to increase productivity
- Back-up plates reinforce all top connectors
- Braces on top step and bottom five steps
- Double riveted slip-resistant Traction-Tred® steps
- Full set of rear horizontals spaced one per foot
- Heavy duty internal spreaders
- Oversized, molded Proguard Boot™ provides firm slip-resistant footing and protect fiberglass rail
- Optional manual pail shelf kit, model no. PK76-9 or automatic closing pail shelf kit model no. PK76-3

SPECIFICATIONS

| FEATURE                                | SIZE / DETAILS   |
|--|--|
| Werner Benefit                         | HolsterTop® with Lock-In System secures tools to increase productivity   |
| Unique Features                        | Works Around Electricity   |
| Size                                   | 10ft   |
| Load Capacity                          | 300lb  |
| Duty Rating                            | Type IA Duty Rating  |
| Style                                  | Single-Sided   |
| Approx. Product Length (in)            | 120  |
| Approx. Product Height (in)            | 6.96   |
| Approx. Product Width (in)             | 28   |
| Approx. Product Depth (in)             | 6  |
| Approx. Product Weight (lb)            | 35.5   |
| Max. Standing Height                   | 7ft 8in  |
| Max. Safe Working Height               | 7ft 8in  |
| Reach Height                           | 14ft   |
| Top Dimension                          | 5.75in x 13in  |
| Approx. Overall Ladder Length (Open)   | 120in  |
| Approx. Overall Ladder Length (Closed) | 8ft  |
| Approx. Closed Length (in)             | 120  |
| Material                               | Fiberglass   |
| Color of Ladder Rail                   | Yellow   |
| Description of Top Features            | Paint tray slot, can hook, Lock-In accessory sockets, 2 tool holes, drill hole, 2 parts trays, tape measure slot, pint, quart and gallon paint can |
| Lock-In Compatible                     | Yes  |
| Certifications                         | ANSI A14.5 (2007), OSHA  |
| Steps/Rung Dimension                   | 3in  |
| Front Flange Dimension                 | 1.18in   |
| Front Rails Dimension                  | 3.125in  |
| Foot Material                          | Plastic with Rubber Pad  |
| Rear Flange Dimension                  | 1.19in   |
| Rear Rails Dimension                   | 1.88in   |
| Spreader Material                      | Steel  |
| Approx. Spread (in)                    | 65.75  |
| Max. Load                              | 300lb  |
| Approx. Shipping Length (in)           | 120  |
| Approx. Shipping Width (in)            | 28   |

|                              |      |
|------------------------------|------|
| Approx. Shipping Height (in) | 6    |
| Approx. Shipping Weight (lb) | 35.5 |
| Approx. Cu. Ft. Per Unit     | 13   |