## Rittal - The System.

Faster – better – everywhere.

## Wallmountedenclosure Stainlesssteel – WM 8017.616

Date: Jul 12, 2017



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

## Wallmounted enclosure Stainless steel – WM 8017.616 - WM202006N4

created: 12.07.2017 build on www.rittal.com/us-en



Produc	ot doc	orinti	^n
Produc	ct aes	Criptic	on

Material: Door: Stainless steel, all-round foamed-in PU seal

Housing and door: Stainless steel 1.4301 (AISI 304)

Mounting plate: Carbon steel, zinc-plated

Surface finish: Brushed

Protection category IP to IEC 60 529:

IP 66

Protection category

NEMA:

NEMA 4X

**Supply includes:** Housing with door(s)

Left hand hinge Mounting plate

Wall mounting blind-nuts

## **Product features**

**Dimensions:** Height: 500 mm (20 ")

Width: 500 mm (20 ") Depth: 150 mm (5.9 ")

Material thickness:: Housing: 1.5 mm (0.06 ")

Door: 1.5 mm (0.06 ")

Mounting plate: 2.5 mm (0.1 ")

Mounting plate: Height: 470 mm (19 ")

Width: 449 mm (18 ")

© Rittal 2017

1

Lock version:	Quarter turn
Packaging unit:	1 pc(s).
Weight/packaging unit:	17 kg (37.5 lb.)
EAN:	83192
Approvals	
Approvals:	UL + C-UL

2017 © Rittal Corporation

© Rittal 2017 2