

# AFC Non-Metallic Whips Type UL

## Specification Description

| Specification              | Non-Metallic Whips                    |
|----------------------------|---------------------------------------|
| Conduit                    | Type LFNC-B, Non-metallic Liquidtight |
| Conductors                 | THHN/THWN<br>8 & 10 AWG               |
| Maximum Temperature Rating | 90°C (dry)<br>75°C (wet)              |
| Grounding                  | NEC® 250.118(1)                       |
| Maximum Voltage Rating     | 600V                                  |

## References & Ratings

- UL File Reference E96572
- NEC® 410, 430, 440, 250, 356
- RoHS Compliant



## Non-metallic Liquidtight Whips (Standard Configurations)

| Product Code | Trade Size (inches) | Length (feet) | No. of Cond. | AWG (cond. size) | Put Up     |
|--------------|---------------------|---------------|--------------|------------------|------------|
| 8014         | 1/2"                | 4'            | 3            | 10               | 10 per box |
| 8015         | 1/2"                | 6'            | 3            | 10               | 10 per box |
| 8016         | 3/4"                | 4'            | 3            | 8                | 10 per box |
| 8017         | 3/4"                | 6'            | 3            | 8                | 8 per box  |
| 8021         | 1/2"                | 4'            | 3            | 10               | 20 bulk    |
| 8022         | 1/2"                | 6'            | 3            | 10               | 15 bulk    |
| 8023         | 3/4"                | 4'            | 3            | 8                | 10 bulk    |
| 8024         | 3/4"                | 6'            | 3            | 8                | 10 bulk    |

Whips come with Black, Red, Green THHN/THWN conductors.

Other conductor colors available by special request.

All whips come with one straight non-metallic liquidtight connector and one 90° angle non-metallic liquidtight connector.