

## Technical Specs

Item	LED Bulb	Light Appearance	5000K and Above, Daylight
Overall Bulb Shape	Cylindrical	Indoor/Outdoor Usage	Indoor/Outdoor
Bulb Shape	Cylindrical	Shatter-Resistant	Yes
Overall Bulb Base Type	Mogul Screw	Rough Service	No
Bulb Base Type	Mogul Screw (EX39)	Bulb Finish	Clear
Light Technology	LED	Bulb Housing	Metal/Polycarbonate
Color Temperature	5000K	Bulb UL Type	Type B
Lumens	10,850 lm	Bulb Power Source	Direct Wired
Wattage Equivalency	250W MH/250W HPS	Light Distribution	Type V
Watts	80 W	For Enclosed Fixtures	Yes
Voltage	120 to 277V AC	Color Rendering Index	83.9
Bulb Beam Angle	120 Degrees	Color Tuning	No
Dimmable	No	Three-Way	No
Bulb Designation	LED/HPS/80W50CG4/E39	High Output	Yes
Bulb Primary Application	Wall Pack	Bulb Minimum Starting Temperature	-40 Degrees F
Bulb Type	High Output	Energy Star Compliant	No
Bulb Dia.	4 3/8 in	Bulb Operating Temp. Range	-40 Degrees to 122 Degrees F
Overall Length	8 3/8 in		
Rated Life	50, 000 hr		

Bulb Manufacturers Warranty Length	5 yr
Standards	cULus, UL 1993