

EF EXTRA FLEXIBLE CONDUIT

LFMC SEALTITE® EF EXTRA FLEXIBLE CONDUIT



SPECIFICATIONS:

- Galvanized steel core with liquid tight PVC jacket
- Color: Gray or Black
- Temp. range: -4°F to +176°F (-20°C to +80°C)
- UV (sunlight) resistant
- Corrosion resistant

APPLICATIONS:

- Applications where no approvals are required

See: www.naed.org www.nema.org
www.anacondasealtite.com

DESCRIPTION:

- Flexible metal core liquid tight conduit
- Designed for applications where no approvals are required
- Also available in black by special order
- Uses standard liquid tight connectors for easy installation
- Additional Put-ups available



Square-Locked Design
3/8" - 2"



| Trade Size (mm) | Item ID | Std. Pkg. (feet) | Inside Diameter (inches) | | Outside Diameter (inches) | | Bend Radius (inches) | Weight (lbs/100 ft) |
|-----------------|---------|------------------|--------------------------|-------|---------------------------|-------|----------------------|---------------------|
| | | | Min | Max | Min | Max | | |
| 3/8" (12) | 39402 | 100 | 0.485 | 0.505 | 0.690 | 0.710 | 2.0 | 21 |
| | 39404 | 800 | | | | | | |
| 1/2" (16) | 39412 | 100 | 0.620 | 0.640 | 0.820 | 0.840 | 2.5 | 25 |
| | 39413 | 1000 | | | | | | |
| | 39414 | 500 | | | | | | |
| 3/4" (21) | 39422 | 100 | 0.815 | 0.835 | 1.030 | 1.050 | 3.0 | 39 |
| | 39428 | 500 | | | | | | |
| | 39429 | 1000 | | | | | | |
| 1" (27) | 39431 | 100 | 1.030 | 1.055 | 1.290 | 1.315 | 4.0 | 51 |
| | 39438 | 400 | | | | | | |
| 1-1/4" (35) | 39441 | 50 | 1.370 | 1.395 | 1.635 | 1.660 | 4.5 | 66 |
| | 39448 | 250 | | | | | | |
| 1-1/2" (41) | 39451 | 50 | 1.575 | 1.600 | 1.865 | 1.900 | 5.5 | 104 |
| | 39454 | 150 | | | | | | |
| 2" (53) | 39461 | 50 | 2.020 | 2.045 | 2.340 | 2.375 | 7.0 | 136 |
| | 39468 | 100 | | | | | | |

FITTINGS FINDER



IP 66/67 with approved fittings

