USA 800.624.4320 | fax 800.799.3779 | *www.gardnerbender.com* **CANADA** 905.564.5749 | fax 905.564.0305

Snap-In Seals ($\frac{1}{2}$ " to 2")

Convenient snap-in feature for quick installation.

- · Zinc-plated to resist corrosion.
- Not waterproof.

| Part # | Pkg Qty | For Knockout Dia. |
|--------|---------|-------------------|
| 601 | 100/box | 1/2" |
| 602 | 100/box | 3/4" |
| 603 | 50/box | 1" |



Galvanized Hanger Strap

For hanging or fastening conduit, pipe or cables.


• Flexible for easy use.



| Part # | Pkg Qty | Description |
|----------|---------|-----------------------|
| GHS-1510 | 1/card | 10' x 3/4" x 26 gauge |

Saf-Te-Plate[™] Protectors

Protects cable and plastic pipe from nail punctures.



| Part # | Pkg Qty | Description |
|---------|---------|--|
| FP159-3 | 100/box | 1½" x 3" x 16 gauge Metal Safety Plate |
| FP159-6 | 50/box | 11/2" x 6" x 16 gauge Metal Safety Plate |

Duct Seal Compound

Seals conduit openings against drafts, dust, moisture and noise.

- Protects terminal boxes, pot heads and bushings from corrosive elements.
- Deadens switch gear panel noise.
- Dough-like compound is easily "thumbed" over holes and gaps.
- Will not harden or form a skin under normal conditions.
- Not for use outdoors.
- · No Silicone.
- · Specifications:
 - Viscosity: ASTM D-217 300-gram load 7.0 -11.0; ASTM DS-S2 100-gram load - 9.0 -15.0
 - Temperature Range: Adheres at -20 °F (-29 °C). Will not slump after 1 hr. at 350 °F (175 °C).
 - Flash Point: Over 550 °F (285 °C).
 - Other Properties: Non-conducting, non-deteriorating, non-toxic, non-corrosive, non-staining, non-curable; 99% solid, coil-based.

| Part # | Pkg Qty | Description |
|--------|---------|-------------|
| DS-130 | 30 pugs | 1 lb Pugs |
| DS-530 | 6 pugs | 5 lb Pugs |

