



Product Number: 62173

Order Abbreviation: MWLPAKN1A/015UNVDSC2/BZ/P

General Description: MiniWallpack, Non-Cutoff, 15W, 120-277V, 0-10V Dim, 80+CRI, CCT Selectable, w/Photocontrol, Bronze Painted, Mini Housing

Product Information

Power Factor	?0.90
Primary Lamp Type	SMD
Minimum Operating Temperature - Celsius	-40
Minimum Operating Temp - Fahrenheit	-40
Total Harmonic Distortion (THD)	? 20 %
Efficacy (LPW)	130
Abbrev. With Packaging Info.	MWLPAKN1A015UNVDSC2BZP 10/CS 1/SKU
Color Temperature/CCT (K)	3000
Ordering Abbreviation	MWLPAKN1A/015UNVDSC2/BZ/P
Average Rated Life 1 (hr)	15000
UPC Code	UPC046135621734
Color Rendering Index (CRI)	80
Service Life Rating	?150000
Lumens (lm)	1950
Wattage (W)	13.00
Color Range	3000 K
Energy Star Rated	No
Fixture Warranty	5 years
Housing	AluminumPolycarbonate (PC)
Luminaire Finish	Bronze
Luminaire Type	Wall pack
Maximum Operating Temperature-Celsius	45
Maximum Operating Temperature-Fahrenheit	113
Dimensions	8.58x5.79x3.07
Certification Listing	CSA, cULus, FCC, RoHS