

## Canopy switches

### Product description

Single-pole, two-circuit  
 1A, 125V/AC; 1A, 250V/AC;  
 3A, 125V/AC; 3A, 250V/AC;  
 6A, 125V/AC; 6A, 250V/AC

### Design features


- Wide variety of sizes for use in fixtures, appliances, doorways and with equipment
- Shank is threaded 15/32"-32 x 15/32" (11.8mm) long
- Hex nut and finishing nut furnished
- 6" (152.4mm) wire lead terminals, #18 105°C stripped 0.75" (19.1mm)



458BD



442



460



449NP

### Pull chain canopy switches



A	Rating V/AC	VL	Description	Color	Catalog no.	
6	125	125	Pull chain with end bell, single-pole, ON-OFF sequence	NP	□ 458NP	•
3	250					
1			Pull chain with end bell, single-pole, ON-OFF sequence	BD	□ 458BD	•

UL Recognized component for US & Canada, file no. E89885

### Pull chain canopy switches



A	Rating V/AC	Description	Color	Catalog no.
3	125 "T"	Single-pole, side wire	NP	□ 442
3	250			
6	250			

UL Recognized component for US & Canada, file no. E89885

### Pull chain canopy switches



A	Rating V/AC	Description	Color	Catalog no.	
3	250	Pull chain with end bell, two-circuit Lo-Med-Hi-OFF sequence	BD	□ 460	•
6	125				

UL Recognized component for US & Canada, file no. E89885


### Push button canopy switches

A	Rating V/AC	VL	Description	Color	Catalog no.
1	250	125	Metal push button, single-pole, ON-OFF sequence	NP	□ 449NP
3					

UL Recognized component for US & Canada, file no. E81103

### Color ordering information:

BD (Brass), NP (Nickel)



**Specification information:** Please visit [www.eaton.com/wiringdevices](http://www.eaton.com/wiringdevices)  
**Compliances, specifications and availability are subject to change without notice.**

RoHS compliant - Page G-21