



PRESTRESSED/CROWN STYLE WET CORE BIT



CONFIGURATION: CONTINUOUS RIM
DIAMOND RATING: +
WELD TYPE: LASER
APPLICATION: PRESTRESSED / PRETENSIONED CONCRETE
 HEAVILY REINFORCED CONCRETE GOOD
 AGGREGATE
 CURED CONCRETE

- UNPARRALLED DRILLING SPEEDS
- ULTRA LONG LIFE
- THIN KERF BIT DESIGN
- USE WET



The Beast/B+BTec Prestressed/Crown Style wet core bits are designed with a thinner kerf that require less bit pressure during operation resulting in faster penetration. They are ideal for use on prestressed/pretensioned concrete and heavily reinforced concrete.

ITEM	DIAMETER	DRILLING DEPTH	ARBOR	SEG/RIM HEIGHT
100058CR	5/8"	13"	5/8"-11 Thread	10mm
100034CR	3/4"	13"	5/8"-11 Thread	10mm
100078CR	7/8"	13"	5/8"-11 Thread	10mm
10010CR	1"	13"	5/8"-11 Thread	10mm
100118CR	1-1/8"	13"	5/8"-11 Thread	10mm
100114CR	1-1/4"	13"	5/8"-11 Thread	10mm
100112CR	1-1/2"	13"	5/8"-11 Thread	10mm
100158CR	1-5/8"	13"	5/8"-11 Thread	10mm
100134CR	1-3/4"	13"	5/8"-11 Thread	10mm
10020CR	2"	13"	1-1/4"-7 Thread	10mm
100212CR	2-1/2"	13"	1-1/4"-7 Thread	10mm
10030CR	3"	13"	1-1/4"-7 Thread	10mm
100312CR	3-1/2"	13"	1-1/4"-7 Thread	10mm
10040CR	4"	13"	1-1/4"-7 Thread	10mm
100412CR	4-1/2"	16"	1-1/4"-7 Thread	11mm
10050CR	5"	16"	1-1/4"-7 Thread	11mm
10060CR	6"	16"	1-1/4"-7 Thread	11mm