



PRO HiSPEED WET CORE BIT

CONFIGURATION: SEGMENTED
DIAMOND RATING: +
WELD TYPE: LASER
APPLICATION: HEAVILY REINFORCED CONCRETE
 HARD AGGREGATE
 CURED CONCRETE
 ASPHALT OVERLAY

- UNPARALLELED DRILLING SPEED
- SUPER LONG LIFE
- IDEAL FOR USE ON HEAVILY REINFORCED CONCRETE
- USE WET



The Beast/B+BTec Hi-Speed wet core bits offer a fantastic drilling performance under any circumstance, but the true nature of these bits is unleashed when drilling in high strength and heavily reinforced concrete. They also work extremely well on hard aggregate.

ITEM	DIAMETER	DRILLING DEPTH	ARBOR	SEG/RIM HEIGHT
10020	2"	16"	1-1/4"-7 Thread	11mm
100212	2-1/2"	16"	1-1/4"-7 Thread	11mm
10030	3"	16"	1-1/4"-7 Thread	11mm
100312	3-1/2"	16"	1-1/4"-7 Thread	11mm
10040	4"	16"	1-1/4"-7 Thread	11mm
100412	4-1/2"	16"	1-1/4"-7 Thread	11mm
10050	5"	16"	1-1/4"-7 Thread	11mm
100514	5-1/4"	16"	1-1/4"-7 Thread	11mm
100512	5-1/2"	16"	1-1/4"-7 Thread	11mm
10060	6"	16"	1-1/4"-7 Thread	11mm
100614	6-1/4"	16"	1-1/4"-7 Thread	11mm
100612	6-1/2"	16"	1-1/4"-7 Thread	11mm
10070	7"	16"	1-1/4"-7 Thread	11mm
10080	8"	16"	1-1/4"-7 Thread	11mm
10090	9"	16"	1-1/4"-7 Thread	11mm
10100	10"	16"	1-1/4"-7 Thread	11mm
10120	12"	16"	1-1/4"-7 Thread	11mm
10140	14"	16"	1-1/4"-7 Thread	11mm
10160	16"	20"	1-1/4"-7 Thread	11mm
10180	18"	20"	1-1/4"-7 Thread	11mm
10200	20"	20"	1-1/4"-7 Thread	11mm
10220	22"	20"	1-1/4"-7 Thread	11mm