

[Return to search](#)[Print Page](#)

**Product Number:** 67516  
**Order Abbreviation:** LU150/55/ECO  
**General Description:** 150W LUMALUX ECOLOGIC high pressure sodium HID lamp, pass Federal TCLP test, E39 based, ET23.5 bulb, universal burn, clear, 2100K

#### Product Information

Abbrev. With Packaging Info.	LU15055ECO 20/CS 1/SKU
ANSI Code	S55
Approx. Lumens (initial - horizontal)	16000
Approx. Lumens (initial - vertical)	16000
Approx. Lumens (mean - horizontal)	13800
Approx. Lumens (mean - vertical)	13800
Arc Length (in)	1.58
Arc Length (mm)	40.2
Average Rated Life - Horizontal (hr)	24000
Average Rated Life - (hr)	24000
Avg Rated Life (hrs)	24000+
Base	E39 Mogul
Bulb	ET23.5
Color Rendering Index (CRI)	22
Color Temperature/CCT (K)	2100
Diameter (in)	2.94
Diameter (mm)	74.6
Family Brand Name	Lumalux® ECO
Fixture Requirement	0
Hot Restrike Time (min)	1 MIN
Lamp Finish	Clear
Light Center Length - LCL (in)	5
Light Center Length - LCL (mm)	127
Maximum Base Temperature - Fahrenheit	482

Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	7.75
Maximum Overall Length - MOL (mm)	197
Nominal Voltage (V)	55.00
Nominal Wattage (W)	150.00
Operating Position	Universal
Warm-up Time (min)	3-4 MINUTES

#### Additional Product Information

##### **Product Documents, Graphs, and Images**

##### **Compatible Ballast**

##### **Packaging Information**



#### Footnotes

- Use with 4000V pulse rated sockets only.
- Passes Federal TCLP test based on NEMA LL Series Standards. TCLP data available upon request. Disposal regulations may vary depending on location. Please check your local and state/provincial regulations.
- 55 Volt lamp.
- Mean lumens measured at 50% of average rated life
- LU150/100 and LU150/55 lamps are not interchangeable.

[Print Page](#)