



GE  
Lighting

16954 - GE Blax® T5 - Facilities; Retail Display; Hospitality; Office;  
Restaurant; Warehouse

F40/30BX/SPX41

## Product Photo



### GENERAL CHARACTERISTICS

Base Type	Pin/Plug-In
Mercury Content	4 mg
Rated Life Hours-nominal	20000 h
Starting Temp (MIN) C-degrees	10 °C
Base Description	4-Pin
Mercury-Picogram per mean lm hr	70.4
Primary Application	Facilities Retail Display Hospitality Office Restaurant Warehouse
Product Technology	Compact Fluorescent
Base	2G11
Bulb Shape	T5

### PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	2840 lm
Nominal Initial Lumen per Watt	79
Initial Lumens-nominal	3150 lm
Color Rendering Index-CRI	82
Color Temperature	4100 K

### PRODUCT INFORMATION

Product Code	16954
Description	F40/30BX/SPX41
Alternative Unit Of Measure	Case
Standard Package Quantity	10
Ean UPC	043168169547
Standard Package GTIN	10043168169544
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
Sales Unit	Unit
UCC	043168169547

### DIMENSIONS

Nominal Length	22.5 in
Bulb Max Overall Length-MOL	22.5 in

### ELECTRICAL CHARACTERISTICS

Equivalent Incandescent Watts	180 W
Rated power (Watts)	40 W

### CAUTIONS & WARNINGS

#### Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

### NOTES

4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).