















# ACCESSORIES

## Mounting Accessories







### SURFACE MOUNT HANGERS

Surface Mount Hangers	Cat. No.	Description	For Use With
	ITB-4	Hanger for mounting close to ceiling on T-Bar grid system	All surface mounted fixtures
	CS-2	Ceiling spacer for mounting directly to outlet box. Used for mounting fixtures below combustible low density cellulose fiberboard ceilings. Maintains 1½" spacing.	All surface mounted fixtures
	CS-4	All purpose spacer (1½" × 2¼" × 4"), maintains 1" spacing on any type of installation	All surface mounted fixtures
	CS-5	All purpose spacer with special T-Bar clip and stud for mounting to an inverted T-Bar ceiling. Maintains 1½" spacing.	All surface mounted fixtures
	CSZT	Zip tee hanger 1½" spacer. Designed for 15/16" wide T-Bars.	CS, LCS, and CSR series except fluorescent HO and VHO models
	KZT	Zip tee hanger 1½" spacer. Designed for 15/16" wide T-Bars.	K and KL
	CSTH	Slide tong hanger for ungrooved channel. Maintains 1½" spacing.	CS, LCS, and CSR (Use KTH for fluorescent HO and VHO)
	KTH	Slide tong hanger with 7/8" hole. Maintains 1½" spacing.	K and KL
	LHVTH	Slide tong hanger with 7/8" hole.	LHV and LHA
	LHSH6	Slide tong hanger with 5/16" holes	LHR 6-Lamp fixtures
	LHSH4	Slide tong hanger with 5/16" holes	LHR 4-Lamp fixtures
	PEBU	End surface mounting bracket for 2H3S hub options	LU, FNPS
	PEBUHMS	End surface mounting bracket for 2H and 2HS hub options	FNPV, FNPS
	PEBA	End surface mounting bracket with 90° adjustment for 2H3S hub options	LU, FNPS
	PEBAHMS	End surface mounting bracket with 90° adjustment for 2H and 2HS hub options	FNPV, FNPS
	PTBS	Surface mounting bracket, 304 Stainless steel, 2 brackets	FNPV, FNPS, FDPS, FNPH, FDPH
	PTBS3	Surface mounting bracket, 304 Stainless steel, 3 brackets	FNPV, FNPS, FDPS, FNPH, FDPH
	PTBA	Surface mounting bracket, 304 Stainless steel, wall mount with 90° adjustment in 15° increments, 2 brackets	FNPV, FNPS, FDPS, FNPH, FDPH
	PTBA3	Surface mounting bracket, 304 Stainless steel, wall mount with 90° adjustment in 15° increments, 3 brackets	FNPV, FNPS, FDPS, FNPH, FDPH
	FSPHB	Top bracket suspension kit, 304 Stainless Steel	FSPH
	FSPHWA	Top bracket wall/angle kit, 304 Stainless Steel	FSPH






# ACCESSORIES

## Mounting Accessories

### CHAIN AND CABLE HANGERS

Chain and Cable Hangers	Cat. No.	Description	For Use With
	XEHC	Chain mount kit includes 14" chain and triangular metal bail for attachment to standard surface mount bracket.	LXEM, XEM
	LUNHK	Chain hanging (chain not included)	LU
	SSHK	Stainless Steel hanging kit (chain not included)	LU
	CSHC	Chain hanging assembly includes two 14" lengths of chain and two hanger hooks.	CS, LCS, and CSR (Use KHC for fluorescent HO or VHO)
	KHC	Chain hanging assembly includes two 24" lengths of chain and two hanger hooks.	K and KL
	ICHC	Chain hanger assembly, #3 size double loop chain, 12'.	IC
	GLH5 GLH10 GLH20	Cable hangers, #2 size cable with loop-end, 5', 10', and 20' lengths, adjustable	All industrials
	LHVQM5 LHVQM10 LHVQM20	Y-Fit Hook Cable Hangers, #2 size cable, 5', 10', and 20' lengths, adjustable	LHV and LHA
	CM24 CM48	Single point mount cable with canopy kit, pair. (Feed and non-feed ends) 24" or 48" with barrel adjuster.	STP. Others may require field drilling of mounting holes.

### PENDANT/STEM MOUNTING ACCESSORIES

Pendant/Stem Mounting	Cat. No.	Description	For Use With
	XEDPM	Kit contains two brackets for pendant hanging with 3/8" threaded rod by others. No drilling of housing is required.	LXEM, XEM
	HUBK	Stem hanging kit consists of two die cast hubs, two "O" rings and locknuts. Hubs are threaded for 1/2" pipe. Housings must be drilled to install hubs.	FNPV, LU, FNPS, FNPH, FDPH
	S18D	Double canopy (2) 18" stems	All 4' LRO, RO, LPT, and PT
	SB3	Stem hanger adaptor bracket for 3-lamp surface mounted units. Reduces total number of mounting points required.	MWW 3-lamp EWW 3-lamp AWW 3-lamp WCW 3-lamp (Use for 3-Lamp fluorescent only; use S18, SS18, C18, S018 for LED and 2-Lamp or 4-Lamp fluorescent)
	S18	Swivel canopy, one 18" stem - all white finish, 8° swivel	Individual or continuous row mounting of most surface and industrial fixtures
	SS18	Swivel canopy, one 18" stem - all white finish, 45° swivel	
	C18	Swivel canopy only - all white finish, 8° swivel	
	S018	One 18" stem only - all white finish	