

Dimmer model numbers

Electronic low-voltage dimmers*

Dimmers

Single-pole	DVELV-300P- CC ³
120V 300W	DVSECELV-300P- CC ⁴
3-way	DVELV-303P- CC ³
120V 300W	DVSECELV-303P- CC ⁴

Only certain LED drivers are dimmable using an ELV dimmer, visit www.lutron.com/LED for more information.

3-wire fluorescent dimmers*

Dimmers

3-way/single-pole	DVF-103P- CC ³
120V 8A	DVSCF-103P- CC ⁴
3-way/single-pole	DVF-103P-277- CC ³
277V 6A	DVSCF-103P-277- CC ⁴

For use with Hi-lume®, Hi-lume® Compact SE, Hi-lume® 3D, Eco-10®, EcoSystem® ballasts.

Also compatible with Hi-lume® LED driver.

No derating required if ganged.

Adjustable low-end trim.

0-10V dimmers

(current sink control)

Dimmers

Single-pole	DVTV- CC ³
30mA max control current	
Single-pole	DVSCTV- CC ⁴
30mA max control current	

Control provides dimming signal only. For dimming with on/off switching, **use with Lutron PowerPack**: PP-120H, PP-277H or PP-347H.

Consult ballast manufacturer for specific ballast current draw to determine maximum number of ballasts per control.

For compatible 0-10V LED drivers by others, visit www.lutron.com/LED.

No derating required if ganged.

Adjustable high-end and low-end trim.

Tu-Wire® fluorescent dimmers

Dimmers

3-way/single-pole	DVFTU-5A3P- CC ³
120V 5A	DVSCFTU-5A3P- CC ⁴

Also compatible with Advance Mark X ballasts, for further information visit www.lutron.com/advance.

For information on use with Universal and OSRAM ballasts, contact Technical Support at 1.800.523.9466.

CC³: Gloss color codes, see pg. 87

CC⁴: Satin color codes, see pg. 87

(Wallplates not included with above, order separately, see pg. 160)

All models must be derated if ganged unless otherwise noted, see pg. 170.
For more information on Lutron ballasts, visit www.lutron.com/ballasts.

***Requires neutral wire connection.**