NON-CONTACT VOLTAGE TESTERS

- \cdot UL Listed
- · CAT IV 1000V AC & CAT IV 600V AC models
- \cdot Dual and Single Range Models
- · IP67 Dust Tight/Water Immersion Protection* (61-657 & 61-647)
- · 2 Meter drop protection (61-657 & 61-647)
- Bright LED forward facing flashlight (3 models)





*Protection against the effects of water immersion in water between 5.9 in. (15cm) and 39.37 (1m) for 30 minutes.



NON-CONTACT VOLTAGE TESTERS

NON-CONTACT VOLTAGE TESTER SELECTION GUIDE	NEW	NEW	NEW	NEW
FEATURES	61-657	61-647	61-637	61-627
CAT Rating (Safety)	CAT IV 1000V	CAT IV 1000V	CAT IV 600V	CAT IV 600V
Listing	cULus, CE, RCM	cULus, CE, RCM	cULus, CE, RCM	cULus, CE, RCM
Voltage Sensing Range	12 ~ 1000V AC	50 ~ 1000V AC	24 ~ 600V AC	50 ~ 600V AC
Dual Range	 ✓ 	_	_	-
Flashlight	 ✓ 	~	~	_
Drop Protection	6.6 ft. (2m)	6.6 ft. (2m)	3.3 ft. (1m)	3.3 ft. (1m)
Ingress Protection	IP67	IP67	_	_
Dual Range Sensitivity	 ✓ 	_	_	-
Audible Indication	 ✓ 	~	~	✓
Audible Defeat	 ✓ 	 ✓ 	 ✓ 	_
Visual Indication	Green On, Flashing Red	Green On, Flashing Red	Green On, Flashing Red	Green On, Flashing Red
Visual Range Indicator	Blue Low, Red High	_	_	-
Lanyard Compatible	 	~	~	 ✓
Auto-Power Off (APO)	 	 ✓ 	 	 ✓
Low Battery Indication	 	 	~	
Battery Type	2 x 1.5V AAA			
Warranty	2-Year	2-Year	2-Year	2-Year



Scan with your smartphone to learn more

P-6044 (5-21) ©2021 IDEAL INDUSTRIES, INC.



Detects AC voltage at outlets (including TR's w/61-657)



Detects AC voltage on conductors



Detects AC voltage at panels



2 x 1.5 AAA Batteries (Included)

IDEAL CUSTOMER SERVICE: orderdesk@idealindustries.com 1-800-824-3325 www.idealind.com

